


The Timken Company

4500 Mt Pleasant St. NW

N. Canton, OH 44720

Phone: (234) 262-3000

E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com
Part Number 23940EMW93W509C08C3, Spherical Roller Bearings - Brass Cage

Spherical bearings are designed to manage high radial loads even when misalignment, poor lubrication, contamination, extreme speeds or critical application stresses are present.




[Specifications](#) | [Dimensions](#) | [Abutment and Fillet Dimensions](#) | [Basic Load Ratings](#) | [Factors](#)

Specifications

Design Unit	Metric
d - Bore	200 mm
Cage Type	EM
Cage Material	Brass
Superseded Part	23940YMW93W509C08C3

Dimensions

D - Outer Diameter	280 mm 11.0236 in
 - Inner Ring Width	60 mm 2.3622 in

B - Outer Ring Width	60 mm 2.3622 in
-----------------------------	--------------------

Abutment and Fillet Dimensions

R - Inner Ring "To Clear" Radius¹	2 mm 0.080 in
---	------------------

r - Outer Ring "To Clear" Radius²	2 mm 0.080 in
---	------------------

da - Inner Ring Backing Diameter	219.000 mm 8.600 in
---	------------------------

Da - Outer Ring Backing Diameter	263 mm 10.3000 in
---	----------------------

Basic Load Ratings

C0 - Static Radial Rating	1130000 N 254000 lbf
----------------------------------	-------------------------

C1(2) - Dynamic Radial Rating (Two-Rows)	712000 N 160000 lbf
---	------------------------

Factors

e - ISO Factor³	0.19
-----------------------------------	------

Y0 - ISO Factor⁴	3.57
------------------------------------	------

Y1 - ISO Factor⁵	3.65
------------------------------------	------

Y2 - ISO Factor⁶	5.43
------------------------------------	------

Reference Thermal Speed Rating (Grease)	1600 rpm
--	----------

Reference Thermal Speed Rating (Oil)⁷	1900 rpm
---	----------

Cg - Geometry Factor⁸	0.1008
---	--------

¹ Maximum housing fillet radius that bearing corners will clear.

² Maximum shaft fillet radius that bearing corners will clear.

³ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.


⁴ These factors apply for both inch and metric calculations. See engineering

⁵ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

⁶ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.


⁷ See thermal speed ratings in the engineering section.

⁸ Geometry constant for Lubrication Life Adjustment Factor a3l.



METRIC UNITS

Number of Rollers Per Row	32
ISO Factor e	0.19
ISO Factor Y0	3.57
ISO Factor Y1	3.65
ISO Factor Y2	5.43
Bearing Weight	11.0 kg
Cage Type	EM
Cage Material	Brass



23940EMW93W509C08C3
SRB ASSEMBLY

THE TIMKEN COMPANY
NORTH CANTON, OHIO USA

Dynamic Radial Rating (Two Rows)	712000	N
Static Radial Rating	1130000	N

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY