



The Timken Company

4500 Mt Pleasant St. NW

N. Canton, OH 44720

Phone: (234) 262-3000

E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com

Part Number 24134KEJW33, Spherical Roller Bearings - Steel Cage

Spherical bearings are designed to manage high radial loads even when misalignment, poor lubrication, contamination, extreme speeds or critical application stresses are present.



[Specifications](#) | [Factors](#) | [Dimensions](#) | [Abutment and Fillet Dimensions](#) | [Basic Load Ratings](#)

Specifications

UPC Code	087796221437
Design Unit	Metric
d - Bore	170 mm
Lubrication Type	Standard Grease
Bore_Taper	1/30
Cage Type	EJ
Cage Material	Steel
Superseded Part	24134KCJW33



e - ISO Factor¹	0.35
Y0 - ISO Factor²	1.88
Y1 - ISO Factor³	1.93
Y2 - ISO Factor⁴	2.87
Reference Thermal Speed Rating (Grease)	960 rpm
Reference Thermal Speed Rating (Oil)⁵	1000 rpm
Cg - Geometry Factor⁶	0.0942

Dimensions

D - Outer Diameter	280 mm 11.0236 in
B' - Inner Ring Width	109 mm 4.2913 in
B - Outer Ring Width	109 mm 4.2913 in

Abutment and Fillet Dimensions

R - Inner Ring "To Clear" Radius⁷	2 mm 0.080 in
r - Outer Ring "To Clear" Radius⁸	2 mm 0.080 in
da - Inner Ring Backing Diameter	192.000 mm 7.5000 in
Da - Outer Ring Backing Diameter	255.000 mm 10.100 in

Basic Load Ratings

C0 - Static Radial Rating	2110000 N 475000 lbf
----------------------------------	-------------------------

C1(2) - Dynamic Radial Rating (Two-Rows)	1440000 N 324000 lbf
---	-------------------------

¹ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

² These factors apply for both inch and metric calculations. See engineering

³ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.


⁴ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

⁵ See thermal speed ratings in the engineering section.

⁶ Geometry constant for Lubrication Life Adjustment Factor a3l.

⁷ Maximum housing fillet radius that bearing corners will clear.

⁸ These maximum fillet radii will be cleared by the bearing corners.



METRIC UNITS

Number of Rollers Per Row	22
ISO Factor e	0.35
ISO Factor Y0	1.88
ISO Factor Y1	1.93
ISO Factor Y2	2.87
Bearing Weight	kg
Cage Type	EJ
Cage Material	Steel
Bore Taper	1/30

TIMKEN®

24134KEJW33
SRB ASSEMBLY

THE TIMKEN COMPANY
NORTH CANTON, OHIO USA

Dynamic Radial Rating (Two Rows)	1440000	N
Static Radial Rating	2110000	N

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY