


**The Timken Company**

4500 Mt Pleasant St. NW


N. Canton, OH 44720

**Phone:** (234) 262-3000

**E-Mail:** [CustomerCAD@timken.com](mailto:CustomerCAD@timken.com) • **Web site:** [www.timken.com](http://www.timken.com)

## Part Number T-5478-C, Inch Sine Bar Gage

- Tapered-bore, antifriction bearings are mounted either on adapter sleeves or on tapered shaft seats.
- In cases where tapered bore bearings are mounted directly on the shaft, the shaft must conform to the tapered bore of the bearing to assure proper fit. If a proper fit is not achieved, the results could be:
  - Turning of the bearing inner race on the shaft.
  - Uneven loading of the bearing.
  - Severe inner race hoop stress.
  - Insufficient support (back-up) of the inner race on the shaft.
- All of these


[more](#)
[Specifications](#) | [Note](#)

### Specifications

<b>Size</b>	8
<b>For Bearings</b>	24089K to 240/630K, 24164K to 24192K

### Note

All sine bars require a sine bar saddle, T-5491-C and a web clamp T-5489-A.



The table above represents the sine bar sizes developed for a full range of tapered bore bearings with

1:12 and a 1:30 taper. Additional sizes are available to fit a variety of width and taper combinations. Consult your local Timken representative for availability.