

## Stainless Steel Spring Retractable Reels

**Air/Water/Oil** - 3/8", 1/2", 3/4", 1" I.D.

Reelcraft's stainless steel hose reels are ideal for food processing, pre-rinse, wash down, chemical transfer and industrial-solvent handling. Also suitable for coastal, offshore and on-board ship in marine applications where the harsh environment of salt water spray requires the use of stainless steel hose reels. Swivels include Viton® O-rings.

**Note:** Standard latch parts are made from aluminium. Series 80000 and D80000 stainless reels have an aluminum fluid path. Stainless latch parts and fluid path are available as a standard option by placing a -S at the end. Example: OLS-S.

### FEATURES

- ✓ Full-flow stainless steel shaft and swivel assures maximum product delivery.  
**Exception:** Series 80000 - only on OLS-S models.
- ✓ Heavy duty brackets eliminate bending due to angular hose pull.
- ✓ Banded drive spring gives smooth automatic hose retrieval.
- ✓ Multi-position guide arm permits wall, floor, ceiling, pit or truck mounting.
- ✓ Nylon guide rollers reduce hose drag and abrasion.
- ✓ Pos-i-latch will maintain the desired working length of hose. Mechanism assures a positive latch of the hose.
- ✓ Series 7000 offers weatherproof gasketed spring motor, assures maximum service life.
- ✓ Vibration-proof self-locking fasteners assures assembly integrity.
- ✓ 304L grade of stainless steel.



Series 7000

## General Use

Many versatile applications in corrosive or sanitary environments



Series D9000

## Ultra Heavy Duty

Heavy duty dual pedestal for maximum strength

Model without hose & bumper	Shipping Weight	Hose I.D.	Hose O.D.	Hose Length	Pressure	(F)NPTF Outlet	(F)NPTF Inlet	Size Index Page	Size Index #
	lbs kg	in mm	in mm	ft m	psi bar	in	in		
<b>Low and Medium Pressure Reels</b> Maximum Temperature 210 °F (99 °C)									
CA 5600 OLS	22 10	3/8 10	.600 15	35 11	500 35	3/8	3/8	9	2
5600 OMS	24 11	3/8 10	.710 18	30 9	3000 207	3/8	3/8	9	2
CS 7800 OLS	41 19	1/2 13	.750 19	50 15	500 35	1/2	1/2	10	----
7600 OMS55	42 19	3/8 10	.710 18	66 20	3000 207	3/8	3/8	10	----
CA 7800 OMS	43 20	1/2 13	.850 22	50 15	3000 207	1/2	1/2	10	----
82000 OLS	81 37	1/2 13	.750 19	100 30	500 35	1/2	1/2	13	1
82000 OMS	83 38	1/2 13	.850 22	75 23	1500 104	1/2	1/2	13	1
83000 OLS	81 37	3/4 19	1.188 30	50 15	500 35	3/4	3/4	13	1
83000 OMS	83 38	3/4 19	1.188 30	50 15	1250 86	3/4	3/4	13	1
D83000 OLS	84 38	3/4 19	1.188 30	75 23	500 35	3/4	3/4	13	2
D84000 OLS	92 42	1 25	1.375 35	50 15	500 35	1	1	13	3
D9200 OLS	115 52	1/2 13	.750 19	100 30	500 35	1/2	1/2	15	1
D9300 OLS	116 53	3/4 19	1.188 30	75 23	500 35	3/4	3/4	15	1
D9400 OLS	117 53	1 25	1.375 35	50 15	500 35	1	1	15	1
D9200 OMS	118 54	1/2 13	.850 22	75 23	3000 207	1/2	1/2	15	1
D9300 OMS	118 54	3/4 19	1.188 30	50 15	3000 207	3/4	3/4	15	1

For all metric thread connections over 1/2" add the suffix number 70 to indicate BSPT threads - example D83000 OLS70. Reference page 6 for guide arm positions.

Model without Hose & bumper	Shipping Weight	Pressure	(F)NPTF Outlet	(F)NPTF Inlet	I.D.	1/4 6	3/8 10	1/2 13	3/4 19	1 25	Size Index #
	lbs kg	psi bar	in	in	O.D.	.530 13	.710 18	.850 22	1.188 30	1.375 35	(see pg. 24)
<b>Manual Crank Medium Pressure Reels</b> Maximum Temperature 210 °F (99 °C)											
CA HS18000 M	36 16	3000 207	1/2	1/2	Hose Length	425 130	300 91	200 61	---	---	1
HS28000 M	35 16	3000 207	1/2	1/2		625 191	450 137	300 91	---	---	2
HS19000 M	38 17	3000 207	3/4	3/4		425 130	300 91	200 61	75 23	---	1
HS29000 M	36 16	3000 207	3/4	3/4		625 191	450 137	300 91	125 38	---	2
HS37000 L	47 21	500 35	1" (M)NPTF	1		---	---	---	---	100 30	refer to reelcraft.com

### Applications

- Restaurants
- Dairies
- Marinas
- Pharmaceutical
- Food processing
- Ships

**Available Options**

**Mounting Brackets**  
See page 47



**Inlet Hose Assemblies**  
See page 49



**Replacement Bumpers**  
See page 49



**Replacement Hoses**  
See page 50

