## **DOCK SEAL - D-150-19**

APPROX WEIGHT: 136.72 lbs

\*\*\* ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE \*\*\* ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON \*OPTIONS: FULL HEIGHT GUIDE STRIPS, (30" STANDARD) 120' 19" 12" 18" HIGH HEADER (12 STANDARD) WITH MOUNTING WOOD 12" HEADER FLAT **HEADER** BOTTOM FOAM BUN / BUMPER PAD **54 OUNCE FACING** 108" SLOPED VERTICAL SIDES DOR INCLINED 96" OR DECLINED DOCK APPROACH MOUNTING BOLT THROUGH BOARD ON EACH SIDE OF ARMOUR PLEATS HEADER 96" TOP THREE FEET 8" EXPOSURE FLAT DOOR (6) JAM BRACKETS FULL HEIGHT 8" EXPOSURE 96' Optional 12" Header Flap FULL HEIGHT 4" EXPOSURE (MOST PROTECTION) NOTE ANY WALL OBSTRUCTIONS WHICH MAY INTERFERE WITH MOUNTING \*AVAILABLE AT ADDITIONAL COSTS UNIT IS SPECIAL AND NON RETURNABLE PERIMETER ANGLE -30" GUIDE STRIPS DIMENSION TOLERANCE ± 1/4" WALL MOUNTING BRACKETS (5) I. THE UNDERSIGNED. AGREE THAT THE PRODUCT AS REPRESENTED SATISFIES DESIGN AND DIMENSION DOCK BUMPERS ARE NOT INCLUDED IN THE SALE OF THE D-150 REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO Α STANDARD FEATURES **CONFIRM PRODUCT AND INSTALLATION** P OPTIONAL FOAM BUN/BUMPER PAD COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE P AND LOCAL REGULATIONS AND STANDARDS. MODEL NUMBER IS D-150-19 R ANY MODIFIED UNITS ARE NON-RETURNABLE **OVERALL WIDTH IS 19"** 0 **OVERALL LENGTH IS 120"** [ ] As drawn [ ] As marked ٧ VENT ON BOTTOM **USABLE LENGTH IS 96"** Α Signed: Date: **OVERALL HEIGHT IS 108"** \*\* ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST **USEABLE HEIGHT IS 96"** Printed Name: BE CORRECTED ON THIS DRAWING, AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE. \*\* LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING DISTRIBUTOR'S NAMF: P.O.# FOR INTERNAL USE ONLY SPECIAL FEATURES PROJECT SIGN OFF VESTIL MANUFACTURING W.O.# **SALES** NONE SALES: X DRAWN BY: **BCN** 2/25/2016 **ENG** REFERENCE: X SCALE: 1:30 FILE NAME: FAB.

POWER

QUOTED LEAD TIME: X

OUOTF #

Χ

35-007-019