Hydraulic Oil, Manifolds and Fittings



▼ Shown top to bottom: **HF-101**, **HF-100**, **HF-102**, **LX-101**, **A65**, and **FZ1055**



HF Oil

- Specially formulated for power pumps
 - maximum volumetric efficiency
 - maximum heat transfer
 - prevents cavitation
 - anti-sludge, anti-rust, anti-foam additives
- Maximum film protective lubricity
 - anti-oxidation additives

LX Hand Pump Oil

- Specially formulated for hand pumps
 - anti-sludge, anti-rust additives
- Reduced handle effort over HF oil
 - good low temperature performance
- Not for use in power pumps

Enerpac System Components

Hydraulic Oil				
Contents	Model Number	High viscosity index ensures maximum lubricity over a wide range of operation		
1 Quart	HF-100	temperatures.		
1 Gallon	HF-101			
5 Gallons*	HF-102			
55 Gallons	HF-104			
1 Gallon**	LX-101			

- * Packed in two 21/2 gallon cans.
- ** Hand pump oil.

▼ Oil Specifications Chart

	HF Oil	LX Oil
ISO Viscosity Grade	32	15
API Gravity, ASTM D1298	32	34
Viscosity, ASTM D445		
SUS @ 212°F	43.7	38
SUS @ 104°F	151	77.5
Viscosity Index, ASTM D2270	95	100
Pour Point, °F, ASTM D97	-36.5	-47.5
Flash Point, °F, ASTM D92	375	370
Color	Blue	Yellow

NOTE: SAE grades do not apply to hydraulic oil.

Manifolds						
Description		Model No.	Dimensions (in)			
7" Long Manifold with 7 female ports.		A-64	3/8"-18NPT (7x) 3.0 2.0 3/8"-18NPT (7x) 8.0 3.25			
14" Long Manifold that allows direct mounting of control valves to the manifold. 7 female ports.	130333	A-65	1.25 1.5 1.5 1.5 1.25 4.0 4.0 4.0 1.25 A-64 A-65			
6-Port Hexagon Manifold Plugs furnished for all ports %"-18 NPTF.		A-66	1.63 82 2.0 25 1/4"-20 3/8"-18NPTF (6x)			
Premounted Manifold Functions as split-flow valve to control 2 to 4 single-acting cylinders simultaneously. All ports %"-18 NPTF.		AM-21 AM-41	4.16 open 3.00 0 .50 0 .			


122

Hydraulic Oil, Manifolds and Fittings



3/8" Swivel Connector

360 degree swivel coupler for optimal orientation of the hydraulic connection on cylinders, pumps and hoses. Order Model No. XSC-1.



A, AM FZ, BFZ, HF, LX



10,000 psi Fittings		Model Number	Dimensions (mm)		Series		100	
Street Elb	ow	6	Number	Α	В	С	D	_ В _
	-NPTF Male -NPTF Female	3	FZ-1616	.94	1.30	3/8"-18 NPTF	3/8"-18 NPTF	DECA
From: %"	Connector -NPTF Female -NPTF Female		FZ-1615	1.13	1.00	3/8"-18 NPTF	1/4"-18 NPTF	C. A
From: ½"	-NPTF Female -NPTF Female		FZ-1625	1.38	1.25	½"-14 NPTF	3⁄8"-18 NPTF	B/
Hexagon I	Nipple							
From:	To:	All III						A - A
1/4"-NPTF	1/4"-NPTF	HHHH	FZ-1608	1.50	.63	1/4"-18 NPTF	1/4"-18 NPTF	С
3/8"-NPTF	3/8"-NPTF		FZ-1619	2.00	.75	3/8"-18 NPTF	3/8"-18 NPTF	, в №
3/8"-NPTF	3/8"-NPTF		FZ-1617	1.47	.75	3/8"-18 NPTF	3/8"-18 NPTF	
From: 3/8"-NPTF	To: 3/8"-NPTF	# 50	FZ-1614	1.14	1.00	3/8"-18 NPTF	3/8"-18 NPTF	C D
1/4"-NPTF	1/4"-NPTF		FZ-1605	1.14	.75	1/4"-18 NPTF	1/4"-18 NPTF	B/ 1
Cross			12-1003	1.14	./5	/4 - 10 NP1F	/4 - 10 NPTF	C
From: %"	-NPTF Female -NPTF Female		FZ-1613	1.77	1.00	3/8"-18 NPTF	-	B
Street Tee								C
From:	To: 3/8"-NPTF	4	FZ-1612	1.77	1.00	3/8"-18 NPTF		
3/8"-NPTF							_	
1/4"-NPTF	1/4"-NPTF	-	FZ-1637	1.77	.94	1/4"-18 NPTF		<u> </u>
	-NPTF Female -NPTF Male		BFZ-16312	2.20	1.02	3/8"-18 NPTF	3/8"-18 NPTF	D C B
Elbow								Δ
From:	To:							
3/8"-NPTF	3/8"-NPTF		FZ-1610	1.38	.88	3/8"-18 NPTF	_	С В
1/4"-NPTF	1/4"-NPTF		FZ-1638	1.41	.94	1/4"-18 NPTF	_	C
Reducer	<u> </u>	7 (2.37)						
From:	To:							A
3/8"- NPTF	1/4"-NPTF		FZ-1630	.75	.75	1/4"-18 NPTF	3⁄8"-18 NPTF	c D
1/4"- NPTF	1/2"-NPTF		BFZ-1630	1.10	.86	1/4"-18 NPTF	½"-14 NPTF	B
3/8"- NPTF	G1⁄4"	_	BFZ-16301	.75	.75	G1/4"	3⁄8"-18 NPTF	
Adaptor	1_							
From:	To:		DET (011)		_			Α
G1/4"	1/4"-NPTF	The same of the sa	BFZ-16411	1.37	.75	1/4"-18 NPTF	G1/4"	
G1/4"	1/8"-NPTF		BFZ-16421	1.22	.75	1/8"-27 NPTF	G1/4"	
G%"	1/4"-NPTF		BFZ-16323	1.69	.94 .94	1/4"-18 NPTF	G%"	<u>B</u> /
G%"	3/8"-NPTF		BFZ-16324	1.69	.54	3/8"-18 NPTF	G%"	
Adaptor								
From:	To:	1						A A
1/4"-18 NPTF	3/8"-18 NPTF	S CHILIN	FZ-1055	1.75	.94	1/4"-18 NPTF	3/8"-18 NPTF	С
½"-14 NPTF	1/4"-18 NPTF		FZ-1633	1.18	.75	1/2"-27 NPTF	1/4"-18 NPTF	
½"-14 NPTF	3%"-18 NPTF		FZ-1634	1.75	1.13	3/8"-18 NPTF	½"-18 NPTF	
	ting -NPTF Male -NPTF Female		FZ-1660	1.59	.88	3⁄8"-18 NPTF	%"-18 №	C B
								I .