



## Buck-Boost Transformer - Three Phase, 220/230/240 - 208V, 45kVA

By Acme Electric  
Catalog # [A3045K0310B](#)

Buck-Boost Transformer - Three Phase, 220/230/240 - 208V, 45kVA



\*Representative Image

### Features

- Copper terminations for trouble free operation
- Lower cost solution
- 5-10 times increase in kVA

### General

Construction	Encapsulated
Max Temperature Rise	115 Degrees Celsius
Mounting Type	Wall
Primary Voltage	220/230/240
Product Category	Buck-Boost Transformer
Secondary Voltage	208 V
UL Insulation Class	180°C
UPC	047503092415
Winding Material	AL
kVA	45

### Dimensions

Dimensions	7.37 in x 19.25 in x 15.21 in
Height	15.21 in
Length	7.37 in
Weight	156 lb
Width	19.25 in

### Electrical Ratings

Frequency Rating	60 Hz
Primary Voltage	240 V

### Certifications and Compliance

CSA Standard	C22.2 No 47
Nema Rating	NEMA 3R
UL Standard	UL 506

### Product Assets

[3D Models - Group\\_27](#)  
[Brochures - 3PhaseBuckBoost](#)  
[Brochures - Buck-Boost Transformers](#)  
[Catalogs - Acme Electric Catalog - Section 7 - Buck Boost Transformers](#)  
[Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice](#)  
[Installation Manuals - Acme Electric Manual A](#)  
[SDS - HCC\\_SDS](#)  
[Terms and Conditions - HCC Terms & Conditions](#)  
[Video - Product Information Video Series - 3 Phase Buck Boost](#)



A proud member of the Hubbell Family.

©2023 Hubbell Incorporated. All rights reserved.  
ACME-A3045K0310B-SPEC-EN | REV 5/2023