

3100-4200 PSI PROFESSIONAL Power Washers

GENERAC®



Tough Cleaning Performance for Any Jobsite

PROFESSIONAL POWER WASHERS

3100 – 4200 PSI

DIRECT DRIVE

Tackle every tough cleaning job at work or on the farm. Generac's rugged power washers combine professional-grade features and user-friendly design. They're a breeze to set up, easy to maneuver and won't let you down.



QUICK-CHANGE NOZZLE TIPS
Five included, for tackling any job

DURABLE WELDED ROLL-CAGE STYLE FRAME
Protects the engine and pump

STEEL-REINFORCED HOSE
Quick-change connectors make hose connections a snap

PROFESSIONAL-GRADE ERGONOMIC SPRAY GUN
Cushion grip handle and easy-to-pull trigger reduce fatigue and improve comfort

PRESSURE CONTROL VALVE
Provides complete control of water pressure for all applications

POWERFUL GENERAC OHV HORIZONTAL-SHAFT ENGINE
Features low-oil shutdown

PROFESSIONAL-GRADE TRIPLEX PUMP
Ceramic-coated pistons mean long life

BELT DRIVE

Powerful. Compact. Long-lasting. These professional-grade power washers feature heavy-duty belt drives for longer pump life than direct drive models. You can also count on a compact, lightweight design for easy mobility around the jobsite.



STEEL-REINFORCED HOSE

Quick-change connectors make hose connections a snap

PROFESSIONAL-GRADE ERGONOMIC SPRAY GUN

Cushion grip handle and easy-to-pull trigger reduce fatigue and improve comfort

HEAVY DUTY BELT DRIVE AR TRIPLEX PUMP

Up to 3X longer life than direct drive triplex pumps

OVERSIZED PNEUMATIC WHEELS

Easily handle rugged jobsite terrain

COMPACT, LIGHTWEIGHT DESIGN

Up to 50 lbs. less weight than other belt-drive power washers

POWERFUL GENERAC OHV HORIZONTAL-SHAFT ENGINE

Features low-oil shutdown



3100-4200 PSI

PROFESSIONAL
POWER WASHERS



SPECIFICATIONS

DIRECT DRIVE	3100 PSI	3600 PSI	3800 PSI	4200 PSI
Model Number (49-State/CARB)	6590 / 6607	6855	6564	6565
GPM	2.8	2.6	3.6	4
Cleaning Power (PSI x GPM)	8680	9360	13680	16800
Engine	212cc Generac OHV w/ low oil shutdown	212cc Generac OHV w/ low oil shutdown	302cc Generac OHV w/ low oil shutdown	420cc Generac OHV w/ low oil shutdown
Pump	Triplex with ceramic-coated pistons & pressure adjustment valve	Triplex with ceramic-coated pistons & pressure adjustment valve	Triplex with ceramic-coated pistons & pressure adjustment valve	Triplex with ceramic-coated pistons & pressure adjustment valve
Spray Gun Type	Professional-grade w/ adjustable side handle	Professional-grade w/ adjustable side handle	Professional-grade w/ adjustable side handle	Professional-grade w/ adjustable side handle
Hose Type	5/16" x 35' steel reinforced	5/16" x 50' steel reinforced	3/8" x 35' steel reinforced	3/8" x 50' steel reinforced
Soap Tanks	Siphon hose	Siphon hose	Siphon hose	Siphon hose
Quick-Connect Nozzle Tips	(5) 0°, 15°, 25°, 40°, soap	(5) 0°, 15°, 25°, 40°, soap	(5) 0°, 15°, 25°, 40°, soap	(5) 0°, 15°, 25°, 40°, soap
Wheel Type	10" never-flat	10" never-flat	10" never-flat	12" pneumatic
Dimensions (L" x W" x H")	31.8 x 24.3 x 38	31.8 x 24.3 x 38	34.5 x 26.8 x 42.5	34.5 x 28.3 x 42.5
Product Weight	102.5 lbs	102.5 lbs	129 lbs	146.5 lbs
Warranty	3 year limited	3 year limited	3 year limited	3 year limited

BELT DRIVE	3800 PSI
Model Number (49-State/CARB)	6712
GPM	3.2
Cleaning Power (PSI x GPM)	12160
Engine	302cc Generac OHV w/ low-oil shutdown
Pump Type	Triplex with ceramic-coated pistons & pressure adjustment valve
Spray Gun Type	Professional-grade w/ adjustable side handle
Hose Type	5/16" x 50' steel reinforced
Quick-Connect Nozzle Tips	(5) 0°, 15°, 25°, 40°, soap
Wheel Type	10" pneumatic
Dimensions (L" x W" x H")	35.5 x 25.25 x 26.75
Product Weight	134 lbs
Warranty	3 year limited

All portable specifications and models subject to change. Please consult factory for availability.