



Pedestal, 2-Gang, Almond

By Hubbell Premise Wiring
Catalog # [FR280ALA](#)

Fire-Rated Poke-Through Pedestal, Double



Features

- 1-4 hour fire rating (1-3 hour for steel floor units and concrete topping, D900 Series Design)
- For 2 ¼ in. to 7 in. floor thickness
- Approved for use in the City of Chicago

Application

Through Floor Delivery

General

| | |
|------------------------------|--|
| Color | Almond |
| Construction | Fabricated |
| Construction Material - Main | 280 Meunt |
| EU RoHS Indicator | No |
| Finish Type | Aluminum |
| Item Type | 2-Gang Above Floor Service Fittings |
| Knockouts | None |
| Material | Aluminum |
| Material - Mounting Hardware | On PT27A Through Floor Fitting |
| Mounting Hardware | Included |
| Mounting Type | On PT27A or PT7XC Through Floor Fitting |
| Performance | Electrical - Service Pedestal Construction - Heavy gauge galvanized steel frame with aluminum housing and face plates |
| Size | Standard Sized Product |
| Style | Pedestals |
| Sub Brand | Accessories |
| Type | Above Floor Service Fittings |
| UPC | 783585396231 |

Dimensions

Display Size Standard Sized Product

Conductor Related

Cable Entry Direct into Device

Certifications and Compliance

Industry Standard(s) UL 514A

Logistics

Carton Quantity 5

Product Assets

Related Products

[SS2309BALA - Pedestal Face Plate, Blank, Aluminum](#)
[SS2309FALA - Pedestal Face Plate, 3/4" KO, Aluminum](#)
[PT27A - 2" Though Floor Fitting](#)



A proud member of the Hubbell Family.

©2023 Hubbell Incorporated. All rights reserved.
PREM-FR280ALA-SPEC-EN | REV 7/2023