

PRODUCT INFORMATION PACKET

Model No: 056T34D15595
Catalog No: K027A
1/2,3450,DP,56,3/60/50/230/460
Open Drip Proof (ODP)



Regal and Marathon are trademarks of Regal Beloit Corporation or one of its affiliated companies.
©2018 Regal Beloit Corporation, All Rights Reserved. MC017097E





Nameplate Specifications

Output HP	0.5 Hp	Output KW	0.37 kW
Frequency	60 Hz	Voltage	230/460 V
Current	1.8/0.9 A	Speed	3450 rpm
Service Factor	1.25	Phase	3
Efficiency	73.3 %	Duty	CONTINUOUS
Insulation Class	B	Design Code	B
KVA Code	N	Frame	56
Enclosure	DP	Overload Protector	NOT
Ambient Temperature	40 °C	Drive End Bearing Size	6203
Opp Drive End Bearing Size	6203	UL	Recognized
CSA	Y	CE	Y
IP Code	22		

Technical Specifications

Electrical Type	SQ CAGE IND RUN	Starting Method	ACROSS THE LINE
Poles	2	Rotation	REV
Mounting	RIGID	Motor Orientation	HORIZONTAL
Drive End Bearing	BALL	Opp Drive End Bearing	BALL
Frame Material	ROLLED STEEL	Shaft Type	STANDARD 56
Overall Length	12.68 in	Frame Length	8.25 in
Shaft Diameter	0.63 in	Shaft Extension	1.88 in
Assembly/Box Mounting	F1 OUT ODE BRKT RADIAL		
Outline Drawing	056T34D15599	Connection Diagram	D0000283-001

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created: 04/05/2018