



<b>Project:</b>	<b>Type:</b>
<b>Prepared By:</b>	<b>Date:</b>

## Technical Specifications

### Performance

**Product Type:**

A-Line

**Input Wattage:**

15.5W

**Wattage Equivalency:**

100W Incandescent

**Lumens:**

1,600lm

**Efficacy:**

93lm/W

**L70 Lifespan:**

15,000 Hours

### Construction

**Bulb Shape:**

A19

**For Use Outdoors in Open Fixtures:**

No

### LED Characteristics

**Color Temperature:**

3000K Warm White

**Color Accuracy (CRI):**

80 CRI

**Beam Angle:**

230°

### Installation

**Base Type:**

GU24

### Electrical

**Power Factor:**

≥0.7

**Operating Temperature:**

-20°C to 45°C (-4°F to 113°F)

**Dimmable:**

Yes, down to 10%

**Input Voltage:**

120V

**Operating Frequency:**

60 Hz

### Other

**Warranty:**

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of three (3) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).

### Compliance

**UL Listed:**

Yes

**Energy Star Approved:**

This product is ENERGY STAR® Version 2.0 Certified

**Energy Star ID:**

2329588


**California Energy Commission (CEC) Status:**

Not Lawful for Sales in California


### Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	15.4	5.2	5
PALLET	2268	47.2	39.4	45.7

### Dimension



### Light Distribution



### Features

- Replacement for High-output Incandescent or lower wattage metal halide and high pressure sodium lamps
- Rated for use in enclosed and open fixtures in dry or damp locations
- Ideal for post top, bollards, and outdoor corridor lighting
- Suitable for use in a base-up or base-down position

### Ordering Matrix

Family	Wattage	Base Type	CRI/Color Temp	Dimmable
A19	16	GU24	830	DIM
	9 = 9W 10 = 10W 13 = 13W 15 = 15W 16 = 16W 5 = 5W 23 = 23W	E26 = E26 Base GU24 = GU24 Base	830 = 80 CRI, 3000K 827 = 80 CRI, 2700K 840 = 80 CRI, 4000K 850 = 80 CRI, 5000K 835 = 80 CRI, 3500K	DIM = Dimmable DIM 120V = Dimmable