

Project:

Type:

Prepared By:

Date:



UPC: 019813834177

Features and Benefits

- Compatible with RAB Type C T8 LED Lamps only
- Meets FCC Part 15 (Class B) Consumer Limits
- Short Circuit Overload and Open Load Protection
- Suitable for Dry and Damp Locations
- UL8750 Recognized Component
- Dimmable with 0-10V Dimmer
- Maximum Case Temperature: 75°C/167°F
- Input Frequency: 50/60 Hz
- THD: < 20%
- Type P
- Output Class 2

Technical Specifications

Electrical

THD:
<20%

Power Factor:
>0.9

Input Voltage:
120-277V AC

Input Frequency:
50/60 Hz

Input Power (Max):
52W

Max. Standby Power:
1W

Output Current:
260mA*4

Max Output Voltage:
30-45V

No-Load Voltage:
56V dc Max.

Efficiency:
>85%

Operating Temperature:
-20°C/-4°F to 45°C/113°F

Dimming:
0-10V Dimming

Construction

Storage Temperature:
-30°C/-22°F to 80°C/176°F

Protection:
Open circuit protection, over voltage protection,
short circuit protection

Reduced Lamp Load:
Parallel output for each channel, support N and N-1
application

Compliance

Certifications:
Class P, UL8750, Output Class 2

Other

Warranty:
RAB warrants that our LED products will be free from
defects in materials and workmanship for a period of
five (5) years from the date of delivery to the end
user, including coverage of light output, color
stability, driver performance and fixture finish. RAB's
warranty is subject to all terms and conditions found
at rablighting.com/warranty.

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	10.7	9.8	10
PALLET	768	38.9	39.8	43.1

Dimension

