



1' x 4' EZPAN edgelit LED panel lights provide smooth and uniform light edge-to-edge for a clean, modern look. Install in drop ceilings or use optional surface, pendant or recessed (dry wall) mounting kits.

Color: White

Weight: 9.3 lbs

| | |
|--------------|-------|
| Project: | Type: |
| Prepared By: | Date: |

| Driver Info | | LED Info | |
|-------------|------------------|----------------|-----------------|
| Type | Constant Current | Watts | 40W |
| 120V | 0.34A | Color Temp | 4000K (Neutral) |
| 208V | 0.20A | Color Accuracy | 82 CRI |
| 240V | 0.17A | L70 Lifespan | 60,000 Hours |
| 277V | 0.15A | Lumens | 4,753 lm |
| Input Watts | 40.4W | Efficacy | 117.6 |

Technical Specifications

Compliance

UL Listed:

Suitable for damp locations

IESNA LM-79 & LM-80 Testing:

RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

CCEA Compliant:

Luminaire Requirements used in Environmental Air Space per the electrical code specification of the City of Chicago

Trade Agreements Act Compliant:

This product is a product of Cambodia and a "designated country" end product that complies with the Trade Agreements Act

DLC Listed:

This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements.
DLC Product Code: P13XIPEG

Performance

Lifespan:

60,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

Wattage Equivalency:

Equivalent to (4)F32T8 or (4)F28T5

Construction

Maximum Ambient Temperature:

Suitable for use in up to -30°C (-22°F) to 50°C(122°F)

IC Rated:

Suitable for insulated ceilings

Lens:

Frosted polystyrene

Housing:

Lightweight aluminum housing, steel pan and junction box

Installation:

Standard integral T-bar clips secure the fixture to T-bars and prevent T-system separation

Finish:

Formulated for high durability and long-lasting color

Green Technology:

Mercury and UV free. RoHS-compliant components.

LED Characteristics

LEDs:

Long-life, high-efficacy, surface-mount LEDs

Installation

Mounting:

Recessed ceiling

Other

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Electrical

Driver:

Constant Current, Class 2, 50/60 Hz, 120-277V, 120V: 0.34A, 208V: 0.20A, 240V: 0.17A, 277V: 0.15A


THD:

8.64% at 120V, 5.93% at 277V

Power Factor:

99.1% at 120V, 94.5% at 277V

Dimensions



Features

- Perfect for shallow plenums
- Even and diffuse ambient illumination, ideal for spaces where glare-free lighting is required
- 0-10V dimmable driver, standard

Ordering Matrix

| Family | Size | | Wattage | Color Temp | Dimming (standard) | Control Options | Other Options |
|---------------|------|----------|---------|-------------------------|--------------------|----------------------|---------------|
| EZPAN | 1X4 | - | 40 | N | /D10 | | |
| 2X4 = 2' x 4' | | 17 = 17W | | Blank = 5000K Cool | | Blank = No Sensor | |
| 2X2 = 2' x 2' | | 30 = 30W | | N = 4000K Neutral | | /LC = Lightcloud | |
| 1X4 = 1' x 4' | | 40 = 40W | | YN = 3500K Warm Neutral | | /E2 = Battery Backup | |
| | | 50 = 50W | | Y = 3000K Warm | | | |