



**The Timken Company**


4500 Mt Pleasant St. NW

N. Canton, OH 44720

**Phone:** (234) 262-3000

**E-Mail:** [CustomerCAD@timken.com](mailto:CustomerCAD@timken.com) • **Web site:** [www.timken.com](http://www.timken.com)

## Part Number QATP15A211S, Single Concentric Top Pull Take-Up Block



[Specifications](#) | [Dimensions](#) | [Radial and Thrust Factors](#) | [Engineering Seal Speed](#) | [Engineering Bearing Attributes](#) | [Engineering Internal Radial Clearance](#)

### Specifications

**Engineering Group** Mounted Bearing

**Bearing Number** 22215

**Shaft Size** 2 11/16 in

**Shaft Size Type** Imperial

**Full Timken Part Number**

- QATP15A211SB
- QATP15A211SC
- QATP15A211SEB
- QATP15A211SEC
- QATP15A211SEM
- QATP15A211SEN
- QATP15A211SEO
- QATP15A211SET
- QATP15A211SM
- QATP15A211SN
- QATP15A211SO



QATP15A211ST

**Locking Style** Single Concentric**Housing Construction** Top Pull Take-Up**Dimensions****Dimension A1** 3.82 in  
97 mm**Dimension B** 3.31 in  
84.1 mm**Dimension C** 4.29 in  
108.9 mm**Dimension D** 8-1/2 in  
215.9 mm**Dimension E** 7.13 in  
181.1 mm**Dimension F** 1.94 in  
49.3 mm**Dimension G** 3.19 in  
81 mm**Dimension H** 3.99 in  
101.4 mm**Dimension J** 1.75 in  
44.4 mm**Dimension K** 1-1/4 in  
31.8 mm**Dimension L** 8-1/2 in  
215.9 mm**Dimension M** 2.37 in  
60.2 mm

<b>Dimension N</b>	3.96 in 100.7 mm
<b>Dimension P</b>	8 in 203.2 mm
<b>Dimension Q</b>	1.06 in 26.9 mm
<b>Dimension RA</b>	0.34 in 8.7 mm
<b>Dimension S</b>	1.12 in 28.4 mm
<b>Dimension TA</b>	3.62 in 92 mm
<b>Dimension U</b>	0.81 in 20.6 mm

### Radial and Thrust Factors

<b>C0 - Static Load</b>	54100 lbf 240000 N
<b>C - Dynamic Load (Basic)</b>	49900 lbf 222000 N
<b>e - Geometry Factor</b>	0.22
<b>Y1 - Geometry Factor</b>	3.14
<b>Y2 - Geometry Factor</b>	4.67

### Engineering Seal Speed

<b>Oil Lubrication - M/N Seal</b>	1600 rpm
<b>Oil Lubrication - T Seal</b>	2900 rpm
<b>Oil Lubrication - B/C/O Seal</b>	1300 rpm

<b>Grease Lubrication - M/N Seal</b>	1600 rpm
--------------------------------------	----------

<b>Grease Lubrication - T Seal</b>	2400 rpm
------------------------------------	----------

<b>Grease Lubrication - B/C/O Seal</b>	1300 rpm
--	----------

### Engineering Bearing Attributes

<b>Float</b>	0.08 in 2.03 mm
--------------	--------------------

<b>Shaft Tolerance</b>	0.0020 in 0.051 mm
------------------------	-----------------------




### Engineering Internal Radial Clearance

<b>Eng Internal Radial Clearance - Min</b>	0.0020
--	--------

<b>Eng Internal Radial Clearance - Max</b>	0.0031
--	--------

<b>Pre Install Clearance Min</b>	0.0020 in 0.050 mm
----------------------------------	-----------------------

<b>Pre Install Clearance Max</b>	0.0031 in 0.080 mm
----------------------------------	-----------------------



Note: Section View not to Scale

C - Dynamic Load	49900	lbf	222000	N
C0 - Static Load	54100	lbf	240000	N
Weight		lb		kg
Max. Speed T-Seals & Grease	2400	rpm		
Rad. Clearance - Max.	0.0031			

**TIMKEN**  
 THE TIMKEN COMPANY  
 NORTH CANTON, OHIO USA

**QATP15A211S**  
 Single Concentric Top Pull Take-Up  
 Block

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

**FOR DISCUSSION ONLY**