

# 3-FLUTE COUNTERSINKS

## G600

- HSS
- 3-Flute
- 90° Countersink with straight shank
- For long reach applications
- Multi-material type excellent for soft to medium steels



Max Dia	Min Dia	Head Length	OAL	Shank Diameter	G600 EDP #
6.3	1.3	6.4	154	5	46381768
8.3	1.8	8.3	155	6	46381769
10.4	2.2	9.7	157	6	46381770
12.4	2.5	10.6	158	8	46381771
15.0	2.8	12.6	159	10	46381772
16.5	2.8	13.9	161	10	46381773
20.5	3.0	17.1	164	10	46381774
25.0	3.2	21.4	168	10	46381775

## G570

- Cobalt
- 3-Flute
- 90° Countersink with straight shank
- AlTiCN coating designed primarily for alloy steels and stainless steels



Max Dia	Min Dia	Head Length	OAL	Shank Diameter	G570 EDP#
6.3	1.5	6.5	45	5	46381760
8.3	2.0	8.2	50	6	46381761
10.4	2.5	9.7	50	6	46381762
12.4	2.8	10.6	56	8	46381763
16.5	3.2	13.9	60	10	46381764
20.5	3.5	17.1	63	10	46381765
25.0	3.8	21.4	67	10	46381766
31.0	4.2	24.4	71	12	46381767

## G400

- Solid Carbide
- 3-Flute
- 90° Countersink with straight shank
- Recommended for abrasive, hard ferrous, and non-ferrous materials



Max Dia	Min Dia	Head Length	OAL	Shank Diameter	G400 EDP#
6.3	1.5	5.0	45	5	0128787
8.3	2.0	6.0	50	6	0128794
10.4	2.5	7.1	50	6	0128725
12.4	2.8	8.0	56	8	0128732
16.5	3.2	10.0	60	10	0128749
20.5	3.5	12.5	63	10	0128756
25.0	3.8	15.0	67	10	0128763
31.0	4.2	18.0	71	12	0128770