



Customer information packet

VXM050542A

0.5HP, 1725RPM, 3PH, 60HZ, 56C, XPFC, F1

Class - CLI GP D; CLII GP F,G

Division - Division I

Specifications

Enclosure	XPFC
Frame	56C
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	CLI GP D; CLII GP F,G
Haz Area Division	Division I
Motor Letter Type	Three Phase
Output @ Frequency	.500 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ 208.0 V @ 60 HZ 230.0 V @ 60 HZ
Agency Approvals	CSA UL
Ambient Temperature	40 °C
Auxillary Box	No Auxillary Box
Auxillary Box Lead Termination	None
Base Indicator	No Mounting
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	1.000 A @ 460.0 V 2.000 A @ 230.0 V 2.100 A @ 208.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	74.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Haz Area Temp Code	T3C
Heater Indicator	No Heater

Part detail

Revision	C
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	34WG1543
Layout	34LY5336
Eff. date	05-01-2024
CD Diagram	CD0007
Poles	04
Leads	12#18
Proprietary	False
Created date	08-07-2020

High Voltage Full Load Amps	1.0 a
Insulation Class	B
Inverter Code	Not Inverter
IP Rating	NONE
KVA Code	L
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3416M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	13.22 IN
Power Factor	63
Product Family	Hazardous Location Motor
Pulley Face Code	C-Face
Rodent Screen	None
Service Factor	1.00
Shaft Diameter	0.625 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Speed	1725 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	Automatic Thermal Overload
Winding Thermal 1 Location	EP
Winding Thermal 2	None

Nameplate

NP0016XPSL									
NO.		CC							
SER. #									
SPEC	34-0000-0391								
CAT.NO.	VXM050542A								
H.P.	.5	T. CODE	T3C						
VOLTS	208-230/460								
AMPS	2.1-2/1								
R.P.M.	1725 34WG1543								
HZ	60	PH	3	CLASS	B				
SER.F.	1.00	DES	B	CODE	L				
RATING	40C AMB-CONT								
FRAME	56C	NEMA NOM. EFF	74						
	PF	63							
BLANK	NEMA MG-1 PART 5, IP54								

AC Induction Motor Performance Data

Record # 6627

Typical performance - not guaranteed values

Winding: 34WG1543-R002			Type: 3416M	Enclosure: XPFC			
Nameplate Data			460 V, 60 Hz: High Voltage Connection				
Rated Output (HP)		.5	Full Load Torque		1.5 LB-FT		
Volts		208-230/460	Start Configuration		direct on line		
Full Load Amps		2.1-2/1	Breakdown Torque		6.5 LB-FT		
R.P.M.		1725	Pull-up Torque		4.5 LB-FT		
Hz	60	Phase	3	Locked-rotor Torque		5.6 LB-FT	
NEMA Design Code		B	KVA Code	L	Starting Current		6.7 A
Service Factor (S.F.)			1	No-load Current		0.89 A	
NEMA Nom. Eff.		74	Power Factor	63	Line-line Res. @ 25°C		33 Ω
Rating - Duty			40C AMB-CONT	Temp. Rise @ Rated Load		59°C	

Load Characteristics 460 V, 60 Hz, 0.5 HP

% of Rated Load	25	50	75	100	125	150
Power Factor	27	39	51	60	67	72
Efficiency	49.8	65	71.7	74.5	75.6	75.5
Speed	1785	1770	1756	1737	1724	1705
Line amperes	0.9	0.94	0.98	1	1.15	1.27


ABB Motors and Mechanical Inc.

WINDING # 34WG1543

Typical performance - not guaranteed values.

0.5 HP 3 PH 60 HZ 1725 RPM 460 V 3416M

TORQUES (LB-FT): PO=6.5 PU=4.5 LR=5.6 LRA=6.7



AC Induction Motor Performance Data

Record # 20790

Typical performance - not guaranteed values

Winding: 34WG1543-R002				Type: 3416M		Enclosure: XPFC	
Nameplate Data				208 V, 60 Hz: Low Voltage Connection			
Rated Output (HP)		.5		Full Load Torque		1.51 LB-FT	
Volts		208-230/460		Start Configuration		direct on line	
Full Load Amps		2.1-2/1		Breakdown Torque		5.25 LB-FT	
R.P.M.		1725		Pull-up Torque		3.56 LB-FT	
Hz	60	Phase	3	Locked-rotor Torque		4.43 LB-FT	
NEMA Design Code		B		KVA Code		L	
Service Factor (S.F.)		1		Starting Current		11.8 A	
NEMA Nom. Eff.		74		Power Factor		63	
Rating - Duty		40C AMB-CONT		Line-line Res. @ 25°C		8.35 Ω	
				Temp. Rise @ Rated Load		50°C	
				Locked-rotor Power Factor		65	
				Rotor inertia		0.0381 LB-FT2	

Load Characteristics 208 V, 60 Hz, 0.5 HP

% of Rated Load	25	50	75	100	125	150
Power Factor	37	52	65	77	79	81
Efficiency	49.3	64.9	71.8	74.4	75.5	75.5
Speed	1782	1765	1748	1725	1707	1683
Line amperes	1.43	1.54	1.67	1.79	2.14	2.47


ABB Motors and Mechanical Inc.


WINDING # 34WG1543

Typical performance - not guaranteed values.



0.5 HP 3 PH 60 HZ 1725 RPM 208 V 3416M

TORQUES (LB-FT): PO=5.25 PU=3.56 LR=4.43 LRA=11.8






CD0007

LOW VOLTAGE
(2Y)

LINE

HIGH VOLTAGE
(1Y)

LINE

NOTES:

1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
2. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY VARY.
3. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

REV. DESC: ADDED "CK" PLANT CODE

REV. LTR: E

BY: EAH

REVISED: 05/06/99 17:1

TDR: 0181040

L00000

FILE: AAA00008370

MDL: -

MTL: -

BALDOR ELECTRIC Co.

3PH, DV, THERMAL, 12 LEADS

CD0007