

## Spring Driven Hose Reels

### Reelcraft® 5000 Series

**Features:**

- reel inlet 3/8" NPTF
- all steel construction
- full shaft and swivel
- furnished standard with PVC hose
- maximum temperature is **150°F**
- Compressed air hose should not be converted to oxygen service; they are often contaminated with an oil coating, which can react explosively when oxygen is introduced. 

**with hose**

Hose ID	Hose Length	Service	PSI	Weight Lbs.	Part #	Price/E
1/4"	50'	air / water	<b>300</b>	26	<b>5450LP</b>	<b>\$742.50</b>
3/8"	35'	air / water	<b>300</b>	25	<b>5635LP</b>	<b>705.70</b>
3/8"	50'	air / water	<b>300</b>	37	<b>5650LP</b>	<b>853.00</b>

**without hose**

Hose Capacity	Service	PSI	Weight Lbs.	Part #	Price/E
50' of 1/4" or 35' of 3/8"	air / water	<b>500</b>	21	<b>5600LP</b>	<b>\$606.50</b>
50' of 3/8"	air / water	<b>500</b>	31	<b>5605LP</b>	<b>708.50</b>

### Reelcraft® 7000 Series

**Features:**

- all steel construction
- LP Low Pressure reels:
  - maximum temperature **150°F**
  - reel inlet 1/2" NPTF
  - PVC hose is standard
- MP Medium Pressure reels:
  - maximum temperature **210°F**
  - reel inlet 1/2" NPTF
  - SAE 100 R1T 1-wire braid hose available
- HP High Pressure reels:
  - maximum temperature **210°F**
  - reel inlet 1/4" NPTF
  - SAE 100 R2T 2-wire braid hose available

**with hose**

Hose ID	Hose Length	Service	PSI	Weight Lbs.	Part #	Price/E
3/8"	70'	air / water	<b>300</b>	50	<b>7670LP</b>	<b>\$1115.45</b>
1/2"	50'	air / water	<b>300</b>	51	<b>7850LP</b>	<b>1091.40</b>

**without hose**

Hose Capacity	Service	PSI	Weight Lbs.	Part #	Price/E
70' of 3/8", 50' of 1/2"	air / water	<b>500</b>	43	<b>7800LP</b>	<b>\$881.25</b>
50' of 3/8" or 50' of 1/2"	oil	<b>3000</b>	44	<b>7800MP</b>	<b>1026.00</b>
50' of 1/4" or 50' of 3/8"	grease	<b>5000</b>	46	<b>7600HP</b>	<b>1184.60</b>

### Reelcraft® 80000 Series

**Features:**

- reel inlet 3/4" NPTF
- five-in-one heat treated aluminum casting incorporates main shaft, ratchet, spring arbor and inlet/outlet plumbing in one-piece casting
- furnished standard with PVC hose
- maximum temperature is **150°F** *with hose*
- maximum temperature is **210°F** *without hose*



see next page for bumper stops,  
consult Dixon for uses  
other than stated services

**with hose**

Hose ID	Hose Length	Service	PSI	Weight Lbs.	Part #	Price/E
1/2"	75'	air / water	<b>300</b>	90	<b>82075LP</b>	<b>\$1680.50</b>
1/2"	100'	air / water	<b>300</b>	99	<b>82100LP</b>	<b>1745.75</b>
3/4"	50'	air / water	<b>250</b>	89	<b>83050LP</b>	<b>1680.50</b>

**without hose**

Hose Capacity	Service	PSI	Weight Lbs.	Part #	Price/E
50' of 3/4" or 100' of 1/2"	air / water	<b>500</b>	74	<b>83000LP</b>	<b>\$1485.00</b>