



*MAXIMUM BUSHING BORE WITH STANDARD KEYWAY

GEOMETRIC TOLERANCE VALUES		THIRD ANGLE PROJECTION	
MM	INCH		
.013	.0005		
.03	.001		
.05	.002		
.08	.003	μm	μin
.13	.005	6.3	250
.20	.008	3.2	125
.25	.010	1.6	63
.38	.015	0.8	32
		0.4	16
		0.2	8

UNLESS OTHERWISE SPECIFIED
 1. METRIC TOLERANCES: X ± 0.8 ; .X ± 0.5 ; .XX ± 0.13
 INCH TOLERANCES: .XX ± 0.02 ; .XXX ± 0.005
 2. ANGLES $\pm 5^\circ$
 3. PRIMARY DIMENSIONS ARE IN MM
 SECONDARY DIMENSIONS ARE IN INCHES
 4. DO NOT SCALE DWG - WORK TO DIMS
 5. PRODUCT MUST CONFORM TO ENGINEERING STANDARD WORK INSTRUCTIONS

nexen Nexen Group, Inc.
 TITLE GENERAL DIMENSIONS
 MODEL TSE-1000*QD'E,6 SPRING
 DWN TRW DATE 1/5/2012 SCALE: 2:3 SHEET 1 OF 1
 CHKD TGH DATE 1/5/2012
 APVD CDV DATE 1/5/2012
 20461 8/21/2014
 ERO ECO DATE
C-822562S

C-822562S