

LIQUIfit™ Fittings

Hose Stems



tube to hose stem

Tube OD	Stem	Nylon Part #	Price/E	Pkg Qty
1/4"	1/4"	63225656WP2	\$2.35	10
3/8"	1/4"	63226056WP2	3.20	10
3/8"	5/16"	63226008WP2	3.50	10
3/8"	3/8"	63226060WP2	3.70	10
1/2"	3/8"	63226260WP2	4.00	10

Plug-in Reducers



tube to plug-in

Tube OD	Plug-in	Nylon Part #	Price/E	Pkg Qty
1/4"	5/16"	63665608WP2	\$3.55	10
1/4"	3/8"	63665660WP2	4.20	10
3/8"	1/2"	63666062WP2	7.60	5

Plug-in Elbows



tube to plug-in

Tube OD	Plug-in	Nylon Part #	Price/E	Pkg Qty
1/4"	1/4"	63825600WP2	\$3.80	10
3/8"	3/8"	63826000WP2	6.40	10
1/2"	1/2"	63826200WP2	7.60	5

Plug-in Tees



tube to tube x plug-in

Tube OD	Plug-in	Nylon Part #	Price/E	Pkg Qty
1/4"	1/4"	63885600WP2	\$5.60	10
3/8"	3/8"	63886000WP2	8.85	10
1/2"	1/2"	63886200WP2	10.70	5

TrueSeal™ Ball Valves**Application:**

These corrosion resistant, all-plastic designed ball valves are ideal for water filtration units, coffee and beverage machines and a wide variety of other fluid applications.

Features:

- EPDM seal secures connection with larger surface area than standard O-rings
- full flow self-cleaning ball
- high-temperature, scale resistant Polysulfone ball
- glass-reinforced Polypropylene body
- FDA compliant
- NSF-51 listed for contact with food

Specifications:

- temperature range: **0°F to 225°F** (-18°C to 107°C)
- O-ring seal material: EPDM
- maximum operating pressure: **150 PSI**
- Burst pressure **600 PSI**
- Actual working pressures will be lower at elevated temperatures.

Valve Male Elbows



tube to male NPTF

Tube OD	Male NPTF	Nylon Part #	Price/E	Pkg Qty
1/4"	1/4"	PP4VME4-MG	\$14.55	10
1/4"	3/8"	PP4VME6-MG	19.00	10
1/4"	1/2"	PP4VME8-MG	23.20	10
3/8"	1/4"	PP6VME4-MG	14.25	10
3/8"	3/8"	PP6VME6-MG	17.15	10
3/8"	1/2"	PP6VME8-MG	24.05	10

Valve Female Elbows



tube to female NPTF

Tube OD	Female NPTF	Nylon Part #	Price/E	Pkg Qty
1/4"	1/4"	PP4VFE4-MG	\$14.90	10
1/4"	3/8"	PP4VFE6-MG	17.15	10
3/8"	1/4"	PP6VFE4-MG	15.85	10
3/8"	3/8"	PP6VFE6-MG	14.25	10