

Straight Ball Drip Valves

Application:

- designed to drain the low point of a system this valve should be placed between a fire department connection and a swing check valve

Features:

- will seal automatically under pressure
- install horizontally
- working pressure: **175 PSI** at 70°F (21°C)

Male NPT	Male NPT	Brass Part #	Price/E
1/2"	1/2"	SBDV50	\$26.60
3/4"	3/4"	SBDV75	30.00




Angled Ball Drip Valves

Features:

- seals automatically under pressure
- installed horizontally, the ball seats at approximately 8-10 PSI
- working pressure: **175 PSI** at 70°F (21°C)

Male NPT	Male NPT	Brass Part #	Price/E
1/2"	1/2"	ASBDV50	\$161.00
3/4"	3/4"	ASBDV75	161.00



Groove x Groove Check Valves

Applications:

- Used in Fire Protection Systems to allow water flow in one direction only. Typical applications include: connections between public water supplies and private fire services systems; discharges from fire pumps; gravity tank connections; fire department pumper connections

Features:

- supplied with 1/4" and 1/2" tapped NPT ports below the clapper and a 1/4" tapped NPT port above the clapper
- supplied with a 1 1/2" NPT tapped boss below the clapper, boss above the clapper may be tapped for the addition of a 1/2" NPT drain
- for horizontal and vertical installation
- U/L listed
- maximum operating pressure: **250 PSI** working pressure at 70°F (21°C)

Description	Brass Part #	Price/E
4" groove x 4" groove	SCVV400	\$364.90



P

Chicago Pattern Valves

Features:

- aluminum handwheel
- maximum operating pressure: **175 PSI** at 70°F (21°C)

Inlet Male NPT	Outlet Male	Cast Brass Part #	Price/E
1 1/2"	1 1/2" NST (NH)	CPV150F	\$363.65
1 1/2"	1 1/2" NPSH	CPV150S	379.35

