

Straight Through Quick-Connect Fittings


Features:

- couplers have no internal valves which provide maximum flow with minimum pressure drop
- Buna-N gasket seal
- interchanges with Parker-Hannifin SST/BST, Foster FST and Hansen ST couplings
- *Do Not Disconnect with pressure in line.*



Female Couplers

Body Size	NPTF Thread	PSI at 70°F	Material	Part #	Price/E	Opt Qty
1/4"	1/4" - 18	5500	brass	STFC2	\$8.38	12
3/8"	3/8" - 18	4500	brass	STFC3	10.33	12
1/2"	1/2" - 14	3500	brass	STFC4	14.92	12
3/4"	3/4" - 14	3100	brass	STFC6	28.69	12
1"	1" - 11 1/2	2500	brass	STFC8	41.31	1
1 1/4"	1 1/4" - 11 1/2	2500	brass	STFC10	111.56	1
1 1/2"	1 1/2" - 11 1/2	2500	brass	STFC12	152.91	1
2"	2" - 11 1/2	2500	brass	STFC16	210.64	1
1/4"	1/4" - 18	6700	303 stainless	STFC2SS	55.25	5
3/8"	3/8" - 18	5500	303 stainless	STFC3SS	80.50	5
1/2"	1/2" - 14	3000	303 stainless	STFC4SS	94.00	5
3/4"	3/4" - 14	3000	303 stainless	STFC6SS	161.25	5
1"	1" - 11 1/2	1700	303 stainless	STFC8SS	218.00	5
1 1/4"	1 1/4" - 11 1/2	2000	303 stainless	10EF10-S	294.22	10
1 1/2"	1 1/2" - 11 1/2	2000	303 stainless	12EF12-S	426.11	5
2"	2" - 11 1/2	2000	303 stainless	16EF16-S	507.30	1



H

Male Couplers

Body Size	NPTF Thread	PSI at 70°F	Material	Part #	Price/E	Opt Qty
1/4"	1/4" - 18	5500	brass	STMC2	\$8.38	12
3/8"	3/8" - 18	4500	brass	STMC3	10.33	12
1/2"	1/2" - 14	3500	brass	STMC4	14.92	12
3/4"	3/4" - 14	3100	brass	STMC6	28.69	12
1"	1" - 11 1/2	2500	brass	STMC8	41.31	1
1 1/4"	1 1/4" - 11 1/2	2500	brass	STMC10	111.56	10
1 1/2"	1 1/2" - 11 1/2	2500	brass	STMC12	152.91	5
2"	2" - 11 1/2	2500	brass	STMC16	210.64	1
1/4"	1/4" - 18	6700	303 stainless	STMC2SS	57.10	5
3/8"	3/8" - 18	5500	303 stainless	STMC3SS	72.00	5
1/2"	1/2" - 14	3000	303 stainless	STMC4SS	99.00	5
3/4"	3/4" - 14	3000	303 stainless	STMC6SS	172.50	5
1"	1" - 11 1/2	1700	303 stainless	STMC8SS	291.25	5



Standard Hose Barb Couplers ¹

Body Size	Hose ID	PSI at 70°F	Material	Part #	Price/E	Opt Qty
1/4"	1/4"	5200	brass	2ES2-B	\$12.45	100
3/8"	3/8"	2800	brass	3ES3-B	13.77	50
1/2"	1/2"	2200	brass	4ES4-B	22.37	25
3/4"	3/4"	1700	brass	6ES6-B	34.43	20
1"	1"	1700	brass	8ES8-B	47.04	10



¹ Operating pressures for the standard hose barbs utilizing hose barb end connections may be dramatically reduced to that of the hose rating and/or hose and end connection combination. Consult hose manufacturer's catalog for hose end connection ratings. If in doubt, test under controlled conditions for suitability to application. Dixon cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.