

Three Way Male Outlet - Roof Connections

Features:


- used to create roof connections, or fire pump test connections
- provides 250 GPM minimum per outlet

back outlet

Pipe Size	(3) Outlets Male	Cast Brass	
		Part #	Price/E
4"	2½" NPT	FR3C4025	\$925.95
6"	2½" NPT	FR3C6025	2072.55
	2½" NST (NH)	FR3C6025F	2197.40

Dimensions

Size	A	B	C
4" x 2½" x 2½" x 2½"	12¾"	8¾"	5¼"
6" x 2½" x 2½" x 2½"	15⅝"	9¾"	7⅝"





bottom outlet

Pipe Size	(3) Outlets Male	Cast Brass	
		Part #	Price/E
4"	2½" NPT	90FR3C4025	\$2071.70
	2½" NST (NH)	90FR3C4025F	2071.70
6"	2½" NPT	90FR3C6025	1404.10
	2½" NST (NH)	90FR3C6025F	1404.10

Dimensions

Size	A	B	C	D
4" x 2½" x 2½" x 2½"	7¾"	11¾"	4-7/16"	6¼"
6" x 2½" x 2½" x 2½"	7¾"	11¾"	4-7/16"	6¼"



Sleeve for Sidewalk (free standing) Connections

Features:

- used in conjunction with a sidewalk escutcheon and a 90° double clapper Siamese to create a sidewalk (free standing) fire department connection
- finishes: -P polished, -C polished chrome plated

Pipe Size	Length	Brass	
		Part #	Price/E
4"	18"	SS418-P	\$589.95
	18"	SS418-C	652.95
	24"	SS424-P	538.40
	24"	SS424-C	630.00
6"	18"	SS618-P	589.95
	18"	SS618-C	813.30
	24"	SS624-P	893.50
	24"	SS624-C	1071.00

