



Customer information packet

CESSWDNM3610T-5

3HP, 3500RPM, 3PH, 60HZ, 182TC, 3646M, TENV, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	TENV
Frame	182TC
Frame Material	Stainless Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	3.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	575.0 V @ 60 HZ
Ambient Temperature	40 °C
Auxillary Box	No Auxillary Box
Auxillary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	2.800 A @ 575.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	89.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	No Endplate
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	2.8 a
Insulation Class	H
Inverter Code	Inverter Ready
KVA Code	R
Lifting Lugs	Standard Lifting Lugs

Part detail

Revision	F
Type	AC
Mech. spec.	36L196
Base	
Status	PRD/A
Elec. spec.	36WGL010
Layout	36LYL196
Eff. date	02-14-2024
CD Diagram	CD0006
Poles	02
Leads	3#16
Proprietary	False
Created date	12-13-2017

Locked Bearing Indicator	Locked Bearing
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	3 @ 16 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3646M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	19.82 IN
Power Factor	91
Product Family	Wash Down Paint Free
Pulley End Bearing Type	Sealed Bearing
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.15
Shaft Diameter	1.125 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	3500 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1669L									
CAT.NO.	CESSWDNM3610T-5								
SPEC.	36L196L010G1								
HP	3								
VOLTS	575								
AMP	2.8								
RPM	3500								
FRAME	182TC		HZ	60		PH	3		
SER.F.	1.15	CODE	R	DES	A	CLASS	H		
NEMA-NOM-EFF	89.5	PF	91						
RATING	40C AMB-CONT								
CC	010A								
DE	6206		ODE	6205					
ENCL	TENV	SN							
BLANK	2:1CT 20:1VT								

AC Induction Motor Performance Data

Record # 58882

Typical performance - not guaranteed values

Winding: 36WGL010-R001		Type: 3646M		Enclosure: TENV	
Nameplate Data			575 V, 60 Hz: Single Voltage Motor		
Rated Output (HP)	3		Full Load Torque	4.58 LB-FT	
Volts	575		Start Configuration	direct on line	
Full Load Amps	2.8		Breakdown Torque	16 LB-FT	
R.P.M.	3500		Pull-up Torque	10.9 LB-FT	
Hz	60	Phase	3	Locked-rotor Torque	13.6 LB-FT
NEMA Design Code	A	KVA Code	R	Starting Current	43.9 A
Service Factor (S.F.)	1.15		No-load Current	0.928 A	
NEMA Nom. Eff.	89.5	Power Factor	91	Line-line Res. @ 25°C	3.86 Ω
Rating - Duty	40C AMB-CONT		Temp. Rise @ Rated Load	92°C	
S.F. Amps			Temp. Rise @ S.F. Load	110°C	
			Locked-rotor Power Factor	41.8	
			Rotor inertia	0.206 LB-FT ²	

Load Characteristics 575 V, 60 Hz, 3 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	62	80	88	91	93	94	92
Efficiency	82.1	88.3	89.5	90	89.5	88.8	89.4
Speed	3574	3553	3530	3506	3481	3454	3490
Line amperes	1.2	1.65	2.2	2.79	3.43	4.1	3.18


ABB Motors and Mechanical Inc.

WINDING # 36WGL010

3 HP 3 PH 60 HZ 3500 RPM 575 V 3646M

Typical performance - not guaranteed values.

TORQUES (LB-FT): PO=16 PU=10.9 LR=13.6 LRA=43.9



4/7/2025 ACPERF, record # 58882

CD0006



NOTES:

1. THREE LEAD MOTOR MAY BE EITHER WYE CONNECTED OR DELTA CONNECTED.
2. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
3. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
4. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY VARY.
5. LEAD COLORS ARE OPTIONAL. LEADS MUST BE NUMBERED AS SHOWN.

CD0006

REV. DESC: ADD CLASS CONN00000007		
REV. LTR: E	VERSION: 01	TDR: 000001099922
FILE: \AAA\00005\141	REVISED: 10:24:49 02/19/2019	BY: ENBRIRO
MTL: -		© □

BALDOR - RELIANCE®

3PH, SV, 3 LEADS, WYE OR DELTA CONNECTED

SH 1 of 1