



Customer information packet

ECTM4111T-G

25HP, 1180RPM, 3PH, 60HZ, 324T, 1260M, TEFC, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	324T
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	25.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1200 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	CSA EEV NEMA PREMIUM NEMA_PREMIUM UR
Ambient Temperature	40 °C
Auxillary Box	No Auxillary Box
Auxillary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	69.000 A @ 208.0 V 63.000 A @ 230.0 V 32.000 A @ 460.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	93.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	Tapped & Key

Part detail

Revision	C
Type	AC
Mech. spec.	12T112
Base	
Status	PRD/A
Elec. spec.	12WGY116
Layout	12LYT112
Eff. date	08-01-2023
CD Diagram	CD0180
Poles	06
Leads	9#8
Proprietary	False
Created date	04-19-2022

Heater Indicator	Heater Included, 115 V
High Voltage Full Load Amps	32.0 a
Insulation Class	F
Inverter Code	Inverter Ready
KVA Code	H
Lifting Lugs	Vertical Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Quantity/Wire Size	9 @ 8 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	1260M
Mounting Arrangement	F1
Number of Poles	6
Overall Length	30.34 IN
Power Factor	79
Product Family	Chemical Processing (Not DC)
Pulley End Bearing Type	Sealed Bearing
Pulley Face Code	Standard
Pulley Shaft Indicator	Tapped & Key
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.15
Shaft Diameter	2.125 IN
Shaft Ground Indicator	Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	1180 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1260									
CAT.NO.	ECTM4111T-G								
SPEC.	12T112Y116G1								
HP	25								
VOLTS	230/460								
AMP	63/32								
RPM	1180								
FRAME	324T		HZ	60		PH		3	
SER.F.	1.15		CODE	H	DES	A		CL	F
NEMA-NOM-EFF	93		PF	79					
RATING	40C AMB-CONT								
CC									
DE	6312		ODE		6311				
ENCL	TEFC	SN							
	INV DUTY 20:1VT								

AC Induction Motor Performance Data

Record # 34363

Typical performance - not guaranteed values

Winding: 12WGY116-R001				Type: 1260M		Enclosure: TEFC	
Nameplate Data				460 V, 60 Hz: High Voltage Connection			
Rated Output (HP)		25		Full Load Torque		111 LB-FT	
Volts		230/460		Start Configuration		direct on line	
Full Load Amps		63/32		Breakdown Torque		308 LB-FT	
R.P.M.		1180		Pull-up Torque		117 LB-FT	
Hz	60	Phase	3	Locked-rotor Torque		171 LB-FT	
NEMA Design Code		A	KVA Code	H	Starting Current		198 A
Service Factor (S.F.)		1.15		No-load Current		13.8 A	
NEMA Nom. Eff.		93	Power Factor	79	Line-line Res. @ 25°C		0.27033 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		46°C	
S.F. Amps				Temp. Rise @ S.F. Load		56°C	
				Locked-rotor Power Factor		28	
				Rotor inertia		11.5 LB-FT2	

Load Characteristics 460 V, 60 Hz, 25 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	43	65	75	79	81	81	80
Efficiency	89.1	92.8	93.5	93.2	92.6	91.5	92.8
Speed	1195.4	1191.8	1188.2	1183.9	1179.3	1172.9	1181
Line amperes	15.6	19.7	25.4	31.9	39.2	49.1	36.3

ABB Motors and Mechanical Inc.

WINDING # 12WGY116

Typical performance - not guaranteed values.

25 HP 3 PH 60 HZ 1180 RPM 460 V 1260M

TORQUES (LB-FT): PO=308 PU=117 LR=171 LRA=198





