

Maximum Rating Tables

Size 821 • GR, NH, EL Series


CAST IRON
GR SERIES

CAST IRON
NH SERIES

ALUMINUM
EL SERIES

Style B

Style H



Size 821

Ratio	Input RPM	Output RPM	Input HP	Output HP	Output Torque (lb-in)	Left Hand Catalog No.	Right Hand Catalog No.	Double Extension Catalog No.	Hollow Output Catalog No.*
5	2500	500	4.305	4.043	510	__8210001	__8210013	__8210025	__8210501.XX
	1750	350	3.653	3.410	614				
	1170	234	2.873	2.657	716				
	100	20	0.433	0.310	977				
7.5	2500	333	3.300	3.051	577	__8210002	__8210014	__8210026	__8210502.XX
	1750	233	2.793	2.562	692				
	1170	156	2.194	1.989	804				
	100	13	0.341	0.230	1089				
10	2500	250	2.973	2.722	686	__8210003	__8210015	__8210027	__8210503.XX
	1750	175	2.464	2.235	805				
	1170	117	1.905	1.702	917				
	100	10	0.300	0.189	1192				
15	2500	166	2.284	2.035	769	__8210004	__8210016	__8210028	__8210504.XX
	1750	116	1.887	1.661	897				
	1170	78	1.459	1.259	1017				
	100	6.7	0.245	0.138	1309				
20	2500	125	1.914	1.642	828	__8210005	__8210017	__8210029	__8210505.XX
	1750	87	1.584	1.338	964				
	1170	58	1.229	1.012	1090				
	100	5.0	0.226	0.111	1397				
25	2500	100	1.623	1.359	857	__8210006	__8210018	__8210030	__8210506.XX
	1750	70	1.333	1.094	985				
	1170	46	1.030	0.820	1104				
	100	4.0	0.200	0.088	1386				
30	2500	83	1.359	1.102	833	__8210007	__8210019	__8210031	__8210507.XX
	1750	58	1.129	0.896	968				
	1170	39	0.882	0.677	1095				
	100	3.3	0.181	0.074	1399				
40	2500	62	1.096	0.829	836	__8210008	__8210020	__8210032	__8210508.XX
	1750	43	0.916	0.674	971				
	1170	29	0.722	0.509	1097				
	100	2.5	0.167	0.056	1401				
50	2500	50	0.925	0.670	845	__8210009	__8210021	__8210033	__8210509.XX
	1750	35	0.769	0.539	970				
	1170	23	0.606	0.403	1086				
	100	2.0	0.149	0.043	1359				
60	2500	41	0.799	0.535	809	__8210010	__8210022	__8210034	__8210510.XX
	1750	29	0.674	0.435	940				
	1170	19	0.539	0.328	1061				
	100	1.7	0.145	0.036	1354				
80	2500	31	0.357	0.236	476	__8210011	__8210023	__8210035	__8210511.XX
	1750	21	0.304	0.190	547				
	1170	14	0.241	0.141	609				
	100	1.3	0.034	0.015	743				
100	2500	25	0.251	0.150	379	__8210012	__8210024	__8210036	__8210512.XX
	1750	17	0.217	0.122	439				
	1170	11	0.175	0.091	491				
	100	1.0	0.026	0.010	605				

How To Build a Part Number For Size GRG821, GRL821, NH821, EL821

1. Select partial catalog number from the selection table
2. Replace leading “__” with series code (GRG, GRL, NH, EL) (see next page for codes)
3. For hollow output, replace “XX” suffix with bore code

Example:

Direct replacement to LEESON IRONMAN, style B, 5:1 ratio, left hand output
GRL-B821-5-L
GRL8210001

GRG = **GROVE GEAR**

- Direct replacement to Grove Gear Flexaline
- Mounting footprint 3.00" x 4.75"
- See pages 52-73 for dimensions

GRL = **IRONMAN** Interchange

- Direct replacement to LEESON IRONMAN & major brands.
- Mounting footprint 2.88" x 5.00"
- See pages 52-73 for dimensions



IRONMAN
BY OHIO GEAR

	Style BM			Style HM	Style BMQ			Style HMQ	
									
NEMA C Input Flange ▲	Left Hand Catalog No.	Right Hand Catalog No.	Double Extension Catalog No.	Hollow Output Catalog No.*	Left Hand Catalog No.	Right Hand Catalog No.	Double Extension Catalog No.	Hollow Output Catalog No.*	Ratio
56C 143-5TC	8210037 8210073	8210049 8210085	8210061 8210097	8210513.XX 8210525.XX	8210109 8210145	8210121 8210157	8210133 8210169	8210537.XX 8210549.XX	5
56C 143-5TC	8210038 8210074	8210050 8210086	8210062 8210098	8210514.XX 8210526.XX	8210110 8210146	8210122 8210158	8210134 8210170	8210538.XX 8210550.XX	7.5
56C 143-5TC	8210039 8210075	8210051 8210087	8210063 8210099	8210515.XX 8210527.XX	8210111 8210147	8210123 8210159	8210135 8210171	8210539.XX 8210551.XX	10
56C 143-5TC	8210040 8210076	8210052 8210088	8210064 8210100	8210516.XX 8210528.XX	8210112 8210148	8210124 8210160	8210136 8210172	8210540.XX 8210552.XX	15
56C 143-5TC	8210041 8210077	8210053 8210089	8210065 8210101	8210517.XX 8210529.XX	8210113 8210149	8210125 8210161	8210137 8210173	8210541.XX 8210553.XX	20
56C 143-5TC	8210042 8210078	8210054 8210090	8210066 8210102	8210518.XX 8210530.XX	8210114 8210150	8210126 8210162	8210138 8210174	8210542.XX 8210554.XX	25
56C 143-5TC	8210043 8210079	8210055 8210091	8210067 8210103	8210519.XX 8210531.XX	8210115 8210151	8210127 8210163	8210139 8210175	8210543.XX 8210555.XX	30
56C 143-5TC	8210044 8210080	8210056 8210092	8210068 8210104	8210520.XX 8210532.XX	8210116 8210152	8210128 8210164	8210140 8210176	8210544.XX 8210556.XX	40
56C 143-5TC	8210045 8210081	8210057 8210093	8210069 8210105	8210521.XX 8210533.XX	8210117 8210153	8210129 8210165	8210141 8210177	8210545.XX 8210557.XX	50
48CZ 56C 143-5TC	8210190 8210046 8210082	8210202 8210058 8210094	8210214 8210070 8210106	8210570.XX 8210522.XX 8210534.XX	8210226 8210118 8210154	8210238 8210130 8210166	8210250 8210142 8210178	8210582.XX 8210546.XX 8210558.XX	60
48CZ 56C	8210191 8210047	8210203 8210059	8210215 8210071	8210571.XX 8210523.XX	8210227 8210119	8210239 8210131	8210251 8210143	8210583.XX 8210547.XX	80
48CZ 56C	8210192 8210048	8210204 8210060	8210216 8210072	8210572.XX 8210524.XX	8210228 8210120	8210240 8210132	8210252 8210144	8210584.XX 8210548.XX	100

For input/ output shaft overhung load and thrust load ratings, refer to pages 419-422.

▲ Consult Factory for other motor flanges available.

* Catalog numbers are for hollow output shaft reducers.

When ordering, substitute the XX suffix with the required output bore code.

Available bore codes

Fraction Size	1"	1-1/8"	1-3/16"	1-1/4"	1-7/16"	1-1/2"
Decimal Size	1.000	1.125	1.188	1.250	1.438	1.500
Output Bore Code	16	18	19	20	23	24

Single Reduction
Worm Gear Reducers

Double Reduction
Worm - Worm Gear Reducers

Double Reduction
Helical - Worm Gear Reducers

WASHGUARD® Reducers
and GEAR+MOTOR™

Ratio Multipliers

Accessories and
Additional Capabilities



NH Series Dimensions Styles: TMQ, TM, T

CAST IRON
NH SERIES

Single Reduction
Worm Gear Reducers

Double Reduction
Worm - Worm Gear Reducers



Double Reduction
Helical - Worm Gear Reducers

WASHGUARD® Reducers
and GEAR+MOTOR™



Ratio Multipliers

Accessories and
Additional Capabilities



Style TMQ




Style TM




Style T




ASSEMBLIES



ASSEMBLIES



ASSEMBLIES



REVERSE ALL ARROWS
FOR OPPOSITE INPUT SHAFT
ROTATION. CONTACT FACTORY
FOR OTHER MOUNTINGS OR
ASSEMBLY POSITIONS.

STYLE TMQ, TM, T DIMENSIONS (Inches)

Size	A	B	C	CA	CD	D	F	G	H	I	J	K	L	M	N	O	O*	V	T +0.000 -0.0015	U +0.000 -0.0015	Input Key*	Output Key
NH813	4.00	5.01	4.97	1.50	1.33	2.03	3.25	1.63	0.28	2.61	4.25	2.13	3.82	1.76	4.00	2.16	1.94	0.31	0.750	0.500	1/8 X 1.00	3/16 X 1.50
NH815	5.25	5.19	5.31	1.50	1.54	2.19	4.50	2.25	0.34	3.14	4.19	2.09	4.35	1.76	4.25	2.56	2.35	0.31	0.750	0.625	3/16 X 1.38	3/16 X 1.50
NH818	4.62	5.89	5.82	1.88	1.75	2.44	3.50	1.75	0.41	3.24	4.63	2.31	4.45	1.76	4.75	2.94	2.73	0.38	1.000	0.625	3/16 X 1.38	1/4 X 1.75
NH821	5.25	5.19	6.31	1.50	2.06	2.63	4.50	2.25	0.34	3.61	4.19	2.09	4.82	1.76	4.34	2.66	2.45	0.31	0.875	0.625	3/16 X 1.38	3/16 X 1.50
NH824	5.25	5.75	7.19	1.50	2.38	3.00	4.50	2.25	0.41	3.77	3.75	1.88	5.51	2.38	4.88	2.91	2.69	0.31	1.000	0.750	3/16 X 1.63	1/4 X 1.75
NH826	6.13	6.51	7.69	2.00	2.63	3.25	4.13	2.06	0.41	4.34	4.75	2.38	6.07	2.38	5.25	3.28	3.07	0.31	1.125	0.750	3/16 X 1.63	1/4 X 1.75
NH830	6.13	7.74	8.56	2.25	3.00	3.69	4.13	2.06	0.41	4.84	6.00	3.00	6.57	2.38	5.77	3.56	3.31	0.31	1.250	0.875	3/16 X 1.63	1/4 X 1.75
NH832	7.50	9.25	10.44	2.50	3.25	4.56	6.50	3.25	0.41	5.02	7.75	3.88	6.76	2.38	7.03	4.24	3.99	0.38	1.500	0.875	3/16 X 1.63	3/8 X 2.25
NH842	6.75	10.99	12.00	2.50	4.25	5.00	5.75	2.88	0.56	6.10	9.75	4.88	9.57	3.47	7.50	3.88	3.59	0.50	1.750	1.250	1/4 X 2.50	3/8 X 2.25
NH852	8.25	13.24	13.82	3.00	5.25	6.00	7.00	3.50	0.69	7.50	12.00	6.00	10.88	3.38	9.00	4.72	4.47	1.13	2.000	1.250	1/4 X 3.00	1/2 X 2.50

Motor Mounting Dimensions

NEMA DIMENSIONS (Inches)

Size	48CZ LM 56C/140TC	180TC/210TC L1	250TC LQ 48CZ/56C/140TC	180TC LQ1 210TC	250TC	48CZ/56C/140TC RQ	180TC 210TC	250TC
NH813	5.63	6.07	N/A	N/A	3.46	N/A	N/A	N/A
NH815	6.16	6.60	N/A	N/A	3.99	N/A	N/A	N/A
NH818	6.26	6.70	N/A	N/A	4.09	N/A	N/A	N/A
NH821	6.63	7.07	N/A	N/A	4.46	N/A	N/A	N/A
NH824	N/A	7.76	8.76	N/A	4.63	5.06	N/A	N/A
NH826	N/A	8.32	9.32	N/A	5.19	5.62	N/A	N/A
NH830	N/A	8.82	9.82	N/A	5.69	6.12	6.56	N/A
NH832	N/A	9.01	10.01	N/A	5.88	6.31	6.75	N/A
NH842	N/A	11.81	12.90	13.46	6.45	7.21	7.21	7.77
NH852	N/A	13.21	14.30	14.86	7.85	8.61	8.61	9.17

NEMA DIMENSIONS (Inches)

Frame	AJ	AK	BD	BE	BE1	Bore Dia.	Keyway	BF
48CZ	3.75	3.00	4.36	0.38	N/A	0.500	1/8 X 1/16	0.28
56C	5.88	4.50	6.50	0.38	N/A	0.625	3/16 X 3/32	0.41
140TC	5.88	4.50	6.50	0.38	N/A	0.875	3/16 X 3/32	0.41
180TC	7.25	8.50	9.00	N/A	0.50	1.125	1/4 X 1/8	0.53
210TC	7.25	8.50	9.00	N/A	0.50	1.375	5/16 X 5/32	0.53
250TC	7.25	8.50	9.00	N/A	0.50	1.625	3/8 X 3/16	0.53

IEC B5 & B3/B5 METRIC DIMENSIONS (Inches)*

Size	D63D	D71D	D80D	D90D	D100LD/ D112MD	D132D	D63D	D71D	D80D	D90D	D100LD/ D112MD	D132D
NH813	2.62	2.65	2.89	N/A	N/A	N/A	2.45	2.47	2.71	N/A	N/A	N/A
NH815	3.15	3.18	3.42	N/A	N/A	N/A	2.98	3.00	3.24	N/A	N/A	N/A
NH818	3.25	3.28	3.52	N/A	N/A	N/A	2.95	2.97	3.21	N/A	N/A	N/A
NH821	3.62	3.65	3.89	N/A	N/A	N/A	3.43	3.44	3.68	N/A	N/A	N/A
NH824	N/A	3.72	4.34	N/A	N/A	N/A	3.46	3.71	N/A	N/A	N/A	N/A
NH826	N/A	4.28	4.90	4.90	5.30	N/A	4.09	4.72	4.72	5.07	N/A	N/A
NH830	N/A	4.78	5.41	5.41	5.80	N/A	4.59	5.22	5.22	5.57	N/A	N/A
NH832	N/A	4.97	5.59	5.59	5.99	N/A	4.78	5.41	5.41	5.76	N/A	N/A
NH842	N/A	N/A	N/A	6.38	6.39	7.17	N/A	N/A	N/A	6.16	6.14	6.93
NH852	N/A	N/A	N/A	7.78	7.78	8.57	N/A	N/A	N/A	7.46	7.45	8.24

IEC B5 & B3/B5 METRIC DIMENSIONS (MM)

Frame	AJ	AK	BD	BE	Bore Dia.	Keyway	BF TAP	OD
D63D	115	95	117	10	11	4 X 2	M8 X 1.25	131
D71D	130	110	132	11	14	5 X 2.5	M8 X 1.25	146
D80D	165	130	165	15	19	6 X 3	M10 X 1.50	184
D90D	165	130	165	15	24	8 X 3.5	M10 X 1.50	184
D100LD/ D112MD	215	180	216	18	28	8 X 3.5	M12 X 1.75	237
D132D	265	230	267	18	38	10 X 4	M12 X 1.75	290

* Applies to double output shaft

◆ Keyway width by depth

■ 48CZ not available

◇ Metric IEC B5 input flange options are available only on quill input styles.

※ Style T and TM only.



For safety, purchaser or user should provide protective guards over shaft extensions and any couplings, sheaves and belts, sprockets and chains, etc., mounted thereon.

GROVE GEAR OE SERIES INTERCHANGE GUIDE

Grove Gear OE Series	Grove Gear IRONMAN NH Series
ZF	TMQ
ZFC	TM
Z	T

Refer to page 8 for complete interchange guide for original Grove Gear OE Series products.