

Chains & sprockets	Wear strips	Side guide brackets & accessories	Levelers
Modular belts & sprockets	Chain & belt return systems	Frame & structure supports	Bearings
Curves & tracks	Side guide solutions	Miscellaneous products	Related information

11120a

800 - 802 - 805

www.SystemPlastSmartGuide.com

Straight running chains double hinge

Extra plus HB
Vacuum hardened stainless steel pins

page code: **711170a**

See also the chains: **11030b**

Click here for related information.



Information about this product is only available on our Smart Guide™ website.

Advantages:

- Very high strength.
- For heavy duty applications.

Item description	Material	Max. working load	Finish μm	Width L		G mm	RD mm	Weight Kg/m
				mm	inch			
SS802-K750	STANDARD	10.300	0,6	190,5	7 ½	1,8	150	5,8
SSE805-K750	Extra plus	15.000	0,3	190,5	7 ½	1,8	150	5,8
SSER805-K750						2,8	75	5,7
SSE805-K750HB	Extra plus HB	15.000				1,8	150	5,8

Sprockets

800 - 802 - 805 - 821

Features:

- Completely closed structure, easier to clean and to disinfect.
- Quick and easy replacement.
- Sprockets and idler wheels made of Steel on request.

Click here for related information.



For chains 821:

11320a

Machined drive sprockets - Split Fixed					
Z	Ø 18*	Ø 25	Ø 30	Ø 35	Ø 40
19	-	800-19R25M-DMS	800-19R30M-DMS	800-19R35M-DMS	800-19R40M-DMS
21	-	800-21R25M-DMS	800-21R30M-DMS	800-21R35M-DMS	800-21R40M-DMS
23	-	800-23R25M-DMS	800-23R30M-DMS	800-23R35M-DMS	800-23R40M-DMS
25	-	800-25R25M-DMS	800-25R30M-DMS	800-25R35M-DMS	800-25R40M-DMS
27	-	800-27R25M-DMS	800-27R30M-DMS	800-27R35M-DMS	800-27R40M-DMS
29	-	800-29R25M-DMS	800-29R30M-DMS	800-29R35M-DMS	800-29R40M-DMS

Machined return sprockets - Split					
Z	Ø 18*	Ø 25	Ø 30	Ø 35	Ø 40
19	800-19R18M-RMS	800-19R25M-RMS	800-19R30M-RMS	800-19R35M-RMS	800-19R40M-RMS
21	800-21R18M-RMS	800-21R25M-RMS	800-21R30M-RMS	800-21R35M-RMS	800-21R40M-RMS
23	800-23R18M-RMS	800-23R25M-RMS	800-23R30M-RMS	800-23R35M-RMS	800-23R40M-RMS
25	800-25R18M-RMS	800-25R25M-RMS	800-25R30M-RMS	800-25R35M-RMS	800-25R40M-RMS
27	800-27R18M-RMS	800-27R25M-RMS	800-27R30M-RMS	800-27R35M-RMS	800-27R40M-RMS
29	800-29R18M-RMS	800-29R25M-RMS	800-29R30M-RMS	800-29R35M-RMS	800-29R40M-RMS



See also the sprockets and idler wheels:

11120b

Z	Ø OD mm	Ø P mm	S mm
19	117	117,34	61,9
21	129	129,26	67,8
23	142	141,21	73,8
25	154	153,21	79,8
27	166,8	165,2	85,8
29	178,5	177,24	91,8

Material: polyamide, screws in stainless steel, nuts in nickel plated brass, DIN 6885 key seat. * Plain Bore