

DS200 Switch-Rated - 200 A

UL/CSA Ratings

- **Max Amperage & Voltage**
200 A, 600 VAC
- **Switch-Rating (AC Only)**
Branch Circuit & Motor Circuit Disconnect Switching
- **Horsepower Ratings**

208 V	3Ø	40 hp
240 V	3Ø	40 hp
480 V	3Ø	100 hp
600 V	3Ø	100 hp
- **Short Circuit Rating**
65 kA Close & Withstand
Testing was performed with RK5 time delay fuses sized at 100% of the device's rated ampacity.

10 kA Close & Withstand
Testing was performed with RK1 current limiting fuses sized at 400% of the highest full load motor ampacity.
- **Environmental Ratings**
Type 4X/IP66/IP67/IP69/IP69K
- **Temperature Range**
Min -40°F/Max 140°F
See pg 254 for temperatures outside of this range.
- **Wiring Capacity**
Based on THHN wire sizes.
Min 4 AWG Max 4/0 AWG
Aux Contacts - Prewired 14 AWG
- **Certifications**
UL 2682, UL 1682,
CSA C22.2 NO. 182.1, NOM

Receptacle (female)

Easy closing drawbar



Inlet (male)



Tabs for latching closing drawbar

! Don't forget to add installation accessories to your order

North American UL/CSA Configurations

VOLTAGE	POLARITY	PART # METAL	PART # METAL
120 V	1P+N+G	37-24165	37-28165
120 208 V	3P+N+G	37-24167	37-28167
125 V	1P+N+G	37-24075	37-28075
125 250 V	2P+N+G	37-24076	37-28076
208 V	2P+G	37-24162	37-28162
208 V	3P+G	37-24163	37-28163
250 V	2P+G	37-24072	37-28072
250 V	3P+G	37-24073	37-28073
277 V	1P+N+G	37-24045	37-28045
277 480 V	3P+N+G	37-24047	37-28047
347 600 V	3P+N+G	37-24147	37-28147
480 V	2P+G	37-24042	37-28042
480 V	3P+G	37-24043	37-28043
600 V	2P+G	37-24142	37-28142
600 V	3P+G	37-24143	37-28143

For international configurations and ratings (IEC, CE) visit meltric.com/international-catalog or contact Customer Service at 800-433-7642.

Main Options



Auxiliary/Pilot Contacts



Mushroom Pawl



Padlock Pawl



Self-Returning Lid

Recommended for cord applications to keep lid tucked in to avoid damage.

! See pages 231-240 for detailed information on these options

RECEPTACLE OPTIONS

SUFFIX

INLET OPTIONS

SUFFIX

With 2 Auxiliary/Pilot Contacts	Recept # -972 ⁴	With 2 Auxiliary/Pilot Contacts	Inlet # -972 ⁷
With 4 Auxiliary/Pilot Contacts	Recept # -174 ⁶	With 4 Auxiliary/Pilot Contacts	Inlet # -174 ³
With 6 Auxiliary/Pilot Contacts	Recept # -976 ⁶	With 6 Auxiliary/Pilot Contacts	Inlet # -976 ³
Straight Insertion	Recept # -A188 ^{2,3}	Self-Ejecting Plug Release**	Inlet # -338-A188 ³
Mushroom Pawl	Recept # -375	For Microswitch	Inlet # -270 ^{3,4}
Padlock Pawl	Recept # -843	Without Lockout Hole	Inlet # -A155
Screw-Type Locking Pawl	Recept # -845	Notes: ** For self-ejecting a -443 suffix must be added to the handle part number. See page 233-234 for more information. ² This option includes the Self-Returning Lid. ³ Not UL/CSA listed. ⁴ Not available on 3P+N+G configurations. ⁶ This option not available with N contact. ⁷ Customers needing to maintain compatibility with old style -172 auxiliary contacts should use a -172 suffix.	
Self-Returning Lid (Manual Close)	Recept # -NC		
With Microswitch	Recept # -270 ^{3,4}		



Order Example: 480 V DS200 + 2 auxiliary contacts
DS200 Metal inlet 3P+G = 37-28043-972




INSTALLATION ACCESSORIES – SIZE 6

When properly installed, all accessories meet or exceed the environmental ratings of the devices they are mounted to; unless otherwise noted.


HANDLES

HANDLE WITH NPT	PART # POLY	PART # METAL
 1"	516P0N10	596P0N10
1 1/4"	516P0N12	596P0N12
1 1/2"	516P0N15	596P0N15
 2"	516P0N20	596P0N20
2 1/2"	516P0N25	596P0N25
3"	-	596P0N30



For available cord grips, see pg 159.


POLY HANDLE WITH CORD GRIP	CABLE RANGE	PART #
	1.520-1.860"	716P0GP2
	1.850-2.190"	716P0GP3*

*May require stripping of cable jacket.

METAL HANDLE WITH CORD GRIP	CABLE RANGE	PART #
	1.688-1.812"	796P0GS1
	1.812-1.938"	796P0GS2*
	1.938-2.062"	796P0JS1
	2.062-2.188"	796P0JS2
	2.188-2.312"	796P0JS3
	2.312-2.438"	796P0JS4*
	2.437-2.625"	796P0KS1
	2.625-2.812"	796P0KS2

*May require stripping of cable jacket.





STRAIGHT HANDLE	CABLE RANGE	PART #	NPT	PART #
 Bolt-on Clamp	1.57-1.97"	5K6P0D50	1 1/2"	5K6P0N15L
	2.01-2.36"	5K6P0D60	2"	5K6P0N20L
 NPT	2.40-2.76"	5K6P0D70	2 1/2"	5K6P0N25L
	2.79-3.15"	5K6P0D80	3"	5K6P0N30L

OVERSIZED METAL HANDLE WITH NPT	PART #
 1 1/2"	796P0N15
2"	796P0N20
2 1/2"	796P0N25
3"	796P0N30


For available cord grips, see pg. 159.

SANTOPRENE HANDLE		
	.984-1.377"	556P0D35
	1.377-1.771"	556P0D45
	1.771-1.929"	556P0D49

ANGLES

METAL ANGLE	PART #
 0°	596M0
 45° Oversized	796M4
	Mounts on oversize metal box only.
 60°	596M6
 60° Extended	597M6

BOXES

METAL ANGLE WITH METAL BOX WITH NPT	PART #
 60° 1 1/2"	796C6N15
60° 2"	796C6N20
* 248.4 in ³ 60° 2 1/2"	796C6N25

* Interior volume with receptacle installed.

METAL BOX WITH NPT	PART #
 0° 1 1/2"	7T6F0N15
0° 2"	7T6F0N20
0° 2 1/2"	7T6F0N25

METAL OVERSIZED BOX WITH NPT	PART #
 0° 2"	7T6F0N20XL
0° 2 1/2"	7T6F0N25XL
0° 3"	7T6F0N30XL

NPT on top or bottom (if rotated). For other configurations, contact Customer Service.


MISCELLANEOUS ACCESSORIES

PROTECTIVE INLET/PLUG CAP	PART #	DESCRIPTION
	39-2A426	Covers lockout hole for watertight seal on inlet. Consult Customer Service for availability. For Inlets/Plugs Only.

PADLOCKABLE INLET/PLUG CAP	PART #	DESCRIPTION
	DS2MC	Aluminum – For Inlets/Plugs Only. -A155 suffix required on inlet part # to retain water ingress protection.

CORD GRIP WITH OPTIONS	PART #
	see pg 159

EASY RETROFIT ADAPTER PLATES	PART #	DESCRIPTION
	see pg 240	Mount to existing boxes.

RECEPTACLE LOCKING PIN	PART #	DESCRIPTION
	LP-843	Requires Padlockable Pawl option (-843) on receptacle.