


Malleable

Images



[Download Photo Image](#)

[Download Dimensional Image](#)

Dimension A in Inches: 2.455

Dimension B in Inches: 1.186

Dimension C in Inches: 5.613

Dimension D in Inches: 4.683

Application

45 Degree connector for use with metallic liquid tight conduit. Insulated Throat - 105°C. Liquidtight connectors are suitable for use in Class I, Div 2; Class II, Div 1 and 2; and Class III, Div 1 and 2 hazardous locations.

Product Information

Material: Malleable Iron

Finish: Zinc Electro-Plate

Certifications & Codes:

Federal Specification Number: A-A-50552

NEMA Standard: FB-1

UL File Number: E9391, cULus

UL Standard: UL-514B

UNSPSC: 39121420

Catalog ID: 459-SLTI

UPC Number: 78174704459

Description: Connector, Liquid Tight, 45 Degree, Malleable Iron, Insulated Throat - 105°C, Size 4 Inch

Application: 45 Degree connector for use with metallic liquid tight conduit. Insulated Throat - 105°C. Liquidtight connectors are suitable for use in Class I, Div 2; Class II, Div 1 and 2; and Class III, Div 1 and 2 hazardous locations.

Trade Size: 4"

Std Pkg Qty: 1