

FAG



22230-E1A-XL-M-C3

Spherical Roller Bearing

Spherical roller bearing 222...-E1A-XL-M,
symmetric 2 outer ribs

X-life

Technical information



Your current product variant

Design	E1A	Without central rip
Bore type	Z	Cylindrical
Cage	M	Brass Cage
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Relubrication feature	Standard	

Main Dimensions & Performance Data

d	150 mm	Bore diameter
D	270 mm	Outside diameter
B	73 mm	Width
C _r	1,010,000 N	Basic dynamic load rating, radial
C _{0r}	1,210,000 N	Basic static load rating, radial
C _{ur}	114,000 N	Fatigue load limit, radial
n _G	2,900 1/min	Limiting speed
n _{gr}	2,050 1/min	Reference speed
≈m	17.661 kg	Weight

Mounting dimensions

d _{a min}	164 mm	Minimum diameter shaft shoulder
D _{a max}	256 mm	Maximum diameter of housing shoulder
r _{a max}	2.5 mm	Maximum recess radius



Dimensions

r _{min}	3 mm	Minimum chamfer dimension
D ₁	240.8 mm	Bore diameter outer ring
d ₂	177.9 mm	Raceway diameter of the inner ring
d _s	8 mm	Diameter lubrication hole
n _s	15 mm	Width of lubricating groove

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0.25	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y ₁	2.69	Dynamic axial load factor
Y ₂	4	Dynamic axial load factor
Y ₀	2.63	Static axial load factor

Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Static angular error and misalignment