


Part Number	KH 6002 E TA
Bearing Size	6002

Bearing Series	KH
Hybrid (Si ₃ N ₄ Balls)	No

Bearing Dimensions

Bore Diameter	d [mm]	15
Outer Diameter	D [mm]	32
Bearing Width	B [mm]	9
Pitch Circle	d _m [mm]	23.5
Ball Diameter	D _w [mm]	3.969
OD Inner Ring	d ₁ [mm]	20.2
OD Inner Ring (Open Side)	d ₂ [mm]	19.4
ID Outer Ring	D ₁ [mm]	26.7
ID Outer Ring (Open Side)	D ₂ [mm]	28.0
Chamfer	r _{1,2} [mm]	0.3
Chamfer (Open Side)	r _{3,4} [mm]	0.3

Geometrical Data

Number of Balls	Z [Qty.]	13
Contact Angle	α ₀ [°]	25
Bearing Weight	m [kg]	0.028

Mating Part Dimensions

Abutment Diameter Inner Ring	d _{a,b} min. [mm]	17.5
Abutment Diameter Outer Ring	D _{a,b} max. [mm]	29.0
Chamfer Associated Component	r _a max. [mm]	0.3
Chamfer Associated Component (Open Side)	r _b max. [mm]	0.1

Bearing Load Ratings

Dynamic Radial Load Rating	C [N]	3,300
Static Radial Load Rating Steel Balls	C ₀ [N]	1,420
Static Radial Load Rating Si ₃ N ₄ balls	C _{0 HY} [N]	1,000

Bearing RPM Ratings

Speed Value with Oil Lubrication	n _{oil} [1/min]	83,000
Speed Value with Grease Lubrication	n _{grease} [1/min]	62,000

Bearing Preload Data

Light Pre-Load	F _v [N]	30
Light Axial Rigidity	C _{ax} [N/μm]	39
Medium Pre-Load	F _v [N]	80
Medium Axial Rigidity	C _{ax} [N/μm]	55
Heavy Pre-Load	F _v [N]	160
Heavy Axial Rigidity	C _{ax} [N/μm]	72
Minimum Spring Pre-Load	F _r [N]	160

Notes:

1. Position of the oiling Nozzle (d_T) for bearings with TA cage/ TXM cage upon request
2. The stated load and speed values are given for a spring preloaded single bearing with oil/air or oil mist lubrication. If specific applications differ, please consult correction factors and/or GMN USA engineers.