


Lead Free Brass Ball Valve

2 Piece, Full Port, Threaded Connection, Long Bonnet Neck, T-Handle, 600 WOG

JF-100TLBG



FEATURES

- Dezincification Resistant Brass Alloy
- Gland Follower and Single O-Ring Stem Design
- Blow-Out Proof Stem
- Long Bonnet Neck for Easier Access in Hard to Reach Applications
- 100% Leak Tested
- 29 in-Hg Vacuum Rating

CERTIFICATIONS/APPROVALS

IAPMO Certified

- NSF/ANSI 372-2020
- NSF/ANSI/CAN 61-2019
- Uniform Plumbing Code (cUPC)
 - IAPMO/ANSI Z1157-2014e1 (R2019)
 - NSF/ANSI 14-2018

Threads conform to ANSI B1.201
MSS SP-110

PRESSURE/TEMPERATURE RATING

600 WOG
Temperature Range: -20° F to 300°F

MATERIALS

No.	Part	Material
1	Body	Lead Free Brass - C46500
2	Seat	PTFE
3	Ball	304 Stainless Steel
4	O-Ring	NBR
5	Extension Sleeve	Brass
6	Packing	PTFE
7	Packing Nut	Brass
8	Handle Nut	Plated Steel
9	Stem	Brass
10	Cap	Lead Free Brass - C46500
11	Handle	Plated Steel

DIMENSIONS

Part No	Size	W	H	L
100-123G	1/2"	2.13	3.47	3.94
100-124G	3/4"	2.4	3.59	3.94