



- NOTES:**
1. ROTATION: RED POSITIVE CCWSE; REVERSIBLE
 2. LEADS: 14 AWG
 3. END PLAY: .005-.030
 4. HIPOT: 1250 VAC FOR ONE SECOND, BOTH LEADS TO CASE
 5. VOLTAGE: 12 VDC
 6. INSULATION: CLASS A 105°C
 7. BEARING SYSTEM: SLEEVE BOTH ENDS
 8. LOAD POINT: 45 ozin @ 2900-3200 RPM

				TOLERANCES UNLESS OTHERWISE SPECIFIED		LEESON ELECTRIC CORPORATION	
				DECIMALS		TRU-TORQ DIVISION 201 N. MISSOURI AVE. SEDALIA, MO 65301 U.S.A. ELECTRIC MOTORS, GEARMOTORS AND DRIVES	
003	DELETED "KELVIN"	1297	JMU	08.30.00		DRAWN DCR 11/24/98	TITLE
002	REVISED LOAD POINT DATA PER LATEST TEST RESULTS	1049	JMU	07.12.00		CH'K'D.	OUTLINE
001	UPDATED TO SHOW FRONT CASTING	1013	AD	6/29/00	.00	APPR.	MATL. &/or CUST.
B	REVISE LABEL & LEAD LENGTH; ADD KEY; REV. NOTE B.	8975	WM	5/7/99	.000	SCALE 1 : 1	12 VDC
A	RELEASE	8821	DCR	12/2/98	.0000	P/C	
REV	DISCRPTION	ECRN	BY	DATE	FRACTIONAL $\pm 1/64$	M/F	
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED					ANGLES $\pm 1/2^\circ$		SIZE
					INCH/MM		DRAWING NO.
							B 970.6000L