

Air Chief A Series Quick-Connect Plugs

Application:

- for use in compressed air service where the convenience of one hand operation and a compact profile is desired

Features:

- maximum operating pressure: **500 PSI** at ambient temperature (70°F)
- machined from solid brass bar stock
- stainless steel balls and springs maximize corrosion resistance

Female Pipe Thread

Body Size	Female NPT	Material	Flow Rating at 100 PSI	Part #	Price/E	Opt Qty
1/8"	1/8"	brass	7 CFM	A1F1-B	\$7.82	20
1/4"	1/4"	brass	25 CFM	A2F2-B	7.82	20



F

Male Pipe Thread

Body Size	Male NPT	Material	Flow Rating at 100 PSI	Part #	Price/E	Opt Qty
1/8"	1/8"	brass	7 CFM	A1M1-B	\$7.82	20
1/4"	1/4"	brass	25 CFM	A2M2-B	7.82	20



Hose Barb

Body Size	Hose ID	Material	Flow Rating at 100 PSI	Part #	Price/E	Opt Qty
1/8"	1/8"	brass	7 CFM	A1S1-B	\$7.82	20



Air Chief A Series Quick-Connect Couplers

automatic - push to connect

Female Pipe Thread

Body Size	Female NPT	Material	Flow Rating at 100 PSI	Part #	Price/E	Opt Qty
1/8"	1/8"	brass	7 CFM	1AF1-B	\$25.49	20
1/4"	1/4"	brass	25 CFM	2AF2-B	26.64	20



Male Pipe Thread

Body Size	Male NPT	Material	Flow Rating at 100 PSI	Part #	Price/E	Opt Qty
1/8"	1/8"	brass	7 CFM	1AM1-B	\$25.49	20
1/4"	1/4"	brass	25 CFM	2AM2-B	26.64	20



Hose Barb

Body Size	Hose ID	Material	Flow Rating at 100 PSI	Part #	Price/E	Opt Qty
1/8"	1/8"	brass	7 CFM	1AS1-B	\$27.80	20
1/4"	1/4"	brass	25 CFM	2AS2-B	28.96	20

