## 300# Single Jacket All Polyester Fire Hose

## Features:

- outer construction: single jacket, all polyester
- tube construction: EPDM rubber lining
- proof pressure: 300 PSI
- service test pressure: 150 PSI at ambient temperature (70°F)
- working pressure: 135 PSI at ambient temperature (70°F)
- consult Dixon for pricing and availability on 25' and 75' lengths, U/L labeled hoses and other threads and configurations

## Uncoupled



Size	Bowl	Length Part #		Price/E
1½"	1-3/4"	50'	A315-50UC	\$174.80
1½"	1-3/4"	100'	A315-100UC	349.60
2"	2-1/4"	50'	A320-50UC	284.95
2"	2-1/4"	100'	A320-100UC	569.90
2½"	2-13/16"	50'	A325-50UC	297.85
2½"	2-13/16"	100'	A325-100UC	595.70
3"	3-3/8"	50'	A330-50UC	478.95
3"	3-3/8"	100'	A330-100UC	958.00

## Coupled with female and male expansion ring couplings



Size	Length	Part #	Rocker Lug Aluminum NST (NH) RAF	Rocker Lug Brass NST (NH) RBF	Pin Lug Brass NST (NH) PBF	Rocker Lug Aluminum NPSH RAS	Rocker Lug Aluminum CT RA_1
1½"	50'	A315-50	\$266.25	\$298.15	\$321.90	\$266.25	
1½"	100'	A315100	452.20	530.35	530.35	452.20	
2"	50"	A320-50				566.60	
2"	100'	A320100				865.95	
21/2"	25'	A325-25					POR
21/2"	50'	A325-50	430.10	562.30	650.00	430.10	POR
2½"	100'	A325100	793.50	902.70	959.80	793.50	POR
3"	50'	A330-50				808.55	
3"	100'	A330100				1311.70	

- <sup>1</sup> Customer Thread *(must specify)* refer to legend on page 566 Consult Dixon for pricing and availability for any of the following options:
- other threads and configurations

P