

Turbo Nozzles

Features:

- 15° spray angle
- maximum temperature: **195°F (91°C)**
- ceramic orifice



Nozzle Size	Description	Orifice	Maximum Working PSI	Part #	Price/E
4.0	1/4" female inlet, dk. green	1.30 mm	3,625	AL-TPR25-30	\$186.00
5.5 - 6.0	1/4" female inlet, purple	1.50 mm	3,625	AL-TPR25-50	186.00
7.0 - 7.5	1/4" female inlet, grey	1.70 mm	3,625	AL-TPR25-70	186.00
4.0	1/4" female inlet, dk. green	1.30 mm	5,075	AL-TPR35-30	282.00
5.5	1/4" female inlet, purple	1.50 mm	5,075	AL-TPR35-50	282.00
6.5	1/4" female inlet, grey	1.70 mm	5,075	AL-TPR35-70	282.00

Nozzle Holders

Feature:

- maximum temperature: **300°F (149°C)**



AL414



AL416

Description	Flow (GPM)	Working PSI	Part #	Price/E
adjustable hi/low nozzle holder with nozzle protector, 1/4" female inlet and outlet	7.8	3,650	AL414	\$47.25
change over nozzle, 1/4" female inlet, 2 each 1/4" female outlets	8	2,900	AL416	64.50

Inlet Filter for Turbo Nozzles

Features:

- 1/4" female inlet, 1/4" male outlet
- maximum temperature: **212°F (100°C)**
- 100 mesh filter



Description	Flow (GPM)	Working PSI	Part #	Price/E
stainless steel, inlet water filter	8	5,000	AR3500	\$38.20