

# Spray Lances and Extensions for Pressure Gun

## Spray Lance

### Features:

- for use with **AL9** spray gun **only**
- maximum operating pressure: **4000 PSI**
- maximum temperature: **300°F**



Part #	Description	Length	Price/E
<b>AL248</b>	<i>zinc</i> , 22 mm x 14 mm male inlet x 1/4" male outlet	24"	<b>\$25.50</b>

## Dual Spray Lances

### Features:

- for use with **HPSG, HPSGC, HPSGHD** and **HPSGW**
- for soap and water
- maximum temperature: **300°F**
- **10.5 GPM**
- requires 1 high pressure nozzle and 1 soap nozzle (pg. 317)
- Allows quick adjustment from high to low pressure with a twist of the handle; low pressure setting allows for use of soap.



AL344



AL333

Part #	Description	Length	Max. Operating PSI	Price/E
<b>AL333</b>	<i>zinc</i> , 1/4" male inlet 2 each 1/4" female outlets	40"	<b>3,650</b>	<b>\$134.00</b>
<b>AL344</b>	<i>stainless steel</i> , 1/4" male inlet, 2 each 1/4" female outlets	40"	<b>4,000</b>	<b>182.75</b>

## Molded Grip Extensions

### Features:

- for use with **HPSG, HPSGC, HPSGHD** and **HPSGW**
- maximum operating pressure: **5000 PSI**
- temperature: **300°F**
- **10.5 GPM** maximum



AL323



AL324



AL325 &amp; AL326

Part #	Description	Length	Price/E
<b>AL323XX</b>	<i>zinc</i> , 1/4" male inlet x 1/4" male outlet	24"	<b>\$21.55</b>
<b>AL324XX</b>	<i>zinc</i> , 1/4" male inlet x 1/4" male outlet, 4" space from the end	36"	<b>24.60</b>
<b>AL325XX</b>	<i>zinc</i> , 1/4" male inlet x 1/4" male outlet, 2 grips	48"	<b>42.90</b>
<b>AL326XX</b>	<i>zinc</i> , 1/4" male inlet x 1/4" male outlet, 2 grips	59"	<b>47.80</b>

## Vented Grip Lances

### Features:

- for use with **HPSG, HPSGC, HPSGHD** and **HPSGW**
- for hot water
- maximum operating pressure: **5000 PSI**
- maximum temperature: **300°F**
- **10.5 GPM** maximum



AL361



AL362

Part #	Description	Length	Price/E
<b>AL361</b>	<i>zinc</i> , 1/4" male inlet x 1/4" female outlet, straight	36"	<b>\$49.90</b>
<b>AL362</b>	<i>zinc</i> , 1/4" male inlet x 1/4" female outlet, bent	48"	<b>73.55</b>