

## D.O.T. Push-In Fittings

## Features:

- materials:
  - body (straights) tube, supports and grippers: brass CA360
  - forged elbows and tees: brass CA377
  - O-ring: Buna-N
- suitable for use up to the maximum working pressure of the plastic tubing used, also suitable for vacuum service
- temperature range: **-40°F to 212°F**
- pre-applied thread sealant (Loctite 516®) on all male pipe threads
- compatible tubing: SAE J844
- meets D.O.T FMVSS 571.106 and SAE J1131, SAE J2494-1 and SAE J2494-3

## Male Elbows



tube to male NPT

Tube OD	Male NPT	Part #	Price/E	Pkg Qty
1/4"	1/8"	<b>AQ69DOT4X2</b>	<b>\$8.95</b>	10
1/4"	1/4"	<b>AQ69DOT4X4</b>	<b>10.15</b>	10
3/8"	1/4"	<b>AQ69DOT6X4</b>	<b>11.40</b>	10

## Swivel Male Elbows



tube to male NPT

Tube OD	Male NPT	Part #	Price/E	Pkg Qty
1/4"	1/8"	<b>AQ69DOTS4X2</b>	<b>\$10.55</b>	10
1/4"	1/4"	<b>AQ69DOTS4X4</b>	<b>11.40</b>	10
1/4"	3/8"	<b>AQ69DOTS4X6</b>	<b>16.45</b>	10
3/8"	1/4"	<b>AQ69DOTS6X4</b>	<b>15.10</b>	10
3/8"	3/8"	<b>AQ69DOTS6X6</b>	<b>17.00</b>	5

## Male Connectors



tube to male NPT

Tube OD	Male NPT	Part #	Price/E	Pkg Qty
1/4"	1/8"	<b>AQ68DOT4X2</b>	<b>\$6.15</b>	10
1/4"	1/4"	<b>AQ68DOT4X4</b>	<b>6.95</b>	10
1/4"	3/8"	<b>AQ68DOT4X6</b>	<b>11.25</b>	5
3/8"	1/4"	<b>AQ68DOT6X4</b>	<b>9.60</b>	10
3/8"	3/8"	<b>AQ68DOT6X6</b>	<b>10.30</b>	10

## Swivel Male Run Tees



tube to male NPT

Tube OD	Male NPT	Part #	Price/E	Pkg Qty
1/4"	1/8"	<b>AQ71DOTS4X2</b>	<b>\$17.95</b>	10
1/4"	1/4"	<b>AQ71DOTS4X4</b>	<b>17.95</b>	5

## Union Connectors



tube to tube

Tube OD	Part #	Price/E	Pkg Qty
1/4"	<b>AQ62DOT4</b>	<b>\$11.45</b>	10
3/8"	<b>AQ62DOT6</b>	<b>13.00</b>	10

## Swivel Male Branch Tees



tube to tube to male NPT

Tube OD	Male NPT	Part #	Price/E	Pkg Qty
1/4"	1/8"	<b>AQ72DOTS4X2</b>	<b>\$17.95</b>	10
1/4"	1/4"	<b>AQ72DOTS4X4</b>	<b>18.80</b>	5

## Union Tees



tube to tube

Tube OD	Part #	Price/E	Pkg Qty
1/4"	<b>AQ64DOT4</b>	<b>\$17.05</b>	10
3/8"	<b>AQ64DOT6</b>	<b>20.80</b>	10