

Sand Blast Couplings

Features:

- designed for use on sand blast hose
- supplied with screws
- nozzle holders have 1¼" NPSM thread
- pressure: 110 PSI at ambient temperature (70°F)
- abrasive blasting equipment must have hose safety cables (page 131) or hose coupling safety locks installed



Installation:

- 1) Ends of hose must be cut square to fit snug against metal end.
- 2) Holding hose tight to end of fitting, insert screws and turn in full, putting screw 180° from first to ensure best centering.
- 3) After all screws have been placed, check tube opposite screws to be sure screws have not penetrated completely through.
- 4) On quick couplings, insert safety clips

Quick Couplings

Hose Size	Hose OD	Brass		Aluminum	
		Part #	Price/E	Part #	Price/E
¾"	1-1/2"	BSB75	\$49.00	ASB75	\$16.10
1"	1-7/8"	BSB100	49.75	ASB100	17.95
1¼"	2-5/32"	BSB125	88.75	ASB125	31.20
1½"	2-3/8"	BSB150	99.50	ASB150	35.35



Nozzle Holders

Hose Size	Hose OD	Brass		Aluminum	
		Part #	Price/E	Part #	Price/E
¾"	1-1/2"	BNH75	\$46.00	ANH75	\$14.75
1"	1-7/8"	BNH100	52.00	ANH100	16.80
1¼"	2-5/32"	BNH125	75.50	ANH125	22.10
1½"	2-3/8"	BNH150	98.00	ANH150	29.25



Threaded Couplings

Hose Size	Brass		Aluminum	
	Part #	Price/E	Part #	Price/E
1¼"	BSC125	\$54.50	ASC125	\$15.90
1½"	BSC150	54.50	ASC150	15.90



Replacement Parts

Part #	Description	Price/E
SBG	black nitrile replacement gasket	\$1.20
USBG	urethane replacement gasket	4.85
SBCS	replacement screw, sold in sets	0.50



SBG



USBG