

Global Forged Angle Hose Valves

**Features:**

- to be used with a fire hose rack assembly, or as a fire department outlet connection
- U/L listed and FM approved
- red steel handwheel
- maximum operating pressure: **300 PSI** at 70°F (21°C)
- polished or chrome plated parts with other outlet threads are also available, consult Dixon for information

Female x Male

Inlet Female NPT	Outlet Male Thread	Forged Brass Part #	Price/E	Wt. Lbs.
1½"	1½" NST (NH)	AV151	\$163.30	4.0
	1½" NYFD	AV151NYFD	163.30	4.0
2½"	2½" NST (NH)	AV251	302.75	8.0
	2½" NYC	AV251NYC	275.35	8.0
	2½" NYFD	AV251NYFD	302.75	8.0

Female x Female

Inlet Female NPT	Outlet Female NPT	Forged Brass Part #	Price/E	Wt. Lbs.
1½"	1½"	AVF151	\$163.30	4.0
2½"	2½"	AVF251	302.75	8.0

Replacement Parts

Description	Part #	Price/E	Wt. Lbs.
handwheel for 1½" valve	AV151-WR	\$32.90	.21
handwheel for 2½" valve	AV251-WR	36.35	1.0
handwheel nut for 1½" valve	AV151-N	1.40	.01
handwheel nut for 2½" valve	AV251-N	1.30	.01
valve seal rubber for 1½" valve	AV151-RBR	16.95	.03
valve seal rubber for 2½" valve	AV251-RBR	15.15	.10

500# Angle Hose Valves



18-157 / 18-158

Applications:

- Typical applications are in fire department, gravity and pressure tank connections, test connections, and public water supplies to sprinkler and standpipe systems; designed and approved to manage 500 PSI pressures in piping systems where it is necessary to access the system for a fire hose connection.

Features:

- red handwheel
- FM approved
- New York City Board of Standards and Appeals, approval # MEA 54-07-E
- maximum operating pressure: **500 PSI** at 70°F (21°C)

Inlet Female NPT	Outlet Male Thread	Cast Brass Part #	Price/E	Wt. Lbs.
2½"	2½" NST (NH)	AV5-250F	\$711.25	12
2½"	2½" NYFD	AV5-250NYFD	711.25	12

Inlet Female NPT	Outlet Female NPT	Cast Brass Part #	Price/E	Wt. Lbs.
2½"	2½"	AVF5-250	\$711.25	12

