




Spring Check Valves



Features:

- 3A authorized 58-00
- full size flow plate
- long stem bushing for increased cycle life
- suitable for low and medium viscosity fluids
- field serviceable (no special tools required)
- operating temperature range: **15°F to 200°F**
- maximum operating pressure: **145 PSI**
- various end connections available, contact Dixon for information

Size	Dimensions				316L Stainless Steel	
	A	B	C	D	Part #	Price/E
½"	0.37"	0.99"	1.10"	1.60"	B45MP-R50	\$392.35
¾"	0.62"	0.99"	1.10"	1.60"	B45MP-R75	440.75
1"	0.87"	1.99"	1.37"	1.92"	B46MP-R100	430.65
1½"	1.37"	1.99"	1.44"	1.92"	B46MP-R150	429.80
2"	1.87"	2.52"	1.44"	1.92"	B46MP-R200	543.55
2½"	2.37"	3.05"	1.44"	1.92"	B46MP-R250	780.50
3"	2.87"	3.58"	1.44"	1.92"	B46MP-R300	1003.20
4"	3.84"	4.69"	1.88"	2.15"	B46MP-R400	1285.40

Repair Kits for Spring Check Valves

Repair kit for ½" - ¾" contains:

- (1) 316L spring
- (1) FKM stem seat
- (1) Buna body O-ring

Repair kit for 1" - 4" contains:

- (1) 316L spring
- (1) FKM stem seat
- (1) Buna clamp gasket

Size	Part #	Price/E
½"	B45MP-RK050	\$18.35
¾"	B45MP-RK075	18.35
1"	B46MP-RK100	29.05
1½"	B46MP-RK150	30.40
2"	B46MP-RK200	36.55
2½"	B46MP-RK250	37.65
3"	B46MP-RK300	47.45
4"	B46MP-RK400	50.15

N