



Series 1 Filter / Regulators

Features:


- particle removal per ISO 8573-1, Class 5 and Class 3
- pressure range 5-150 PSI
- in-line or modular installation
- 40 micron element
- 2 oz. reservoir
- quick-release bayonet bowl
- prismatic lens liquid level indicator
- supplied with GC620 gauge
- inlet pressure:
 - transparent bowl: **150 PSI** at ambient temperature (70°F)
 - metal bowl: **250 PSI** at ambient temperature (70°F)




1/4 Turn Manual Drain
** minimum clearance required to remove bowl




Semi auto Drain
** minimum clearance required to remove bowl




1/4 Turn Manual Drain
** minimum clearance required to remove bowl



Automatic Drain
** minimum clearance required to remove bowl



Manual Drain
** minimum clearance required to remove bowl



Automatic Drain
** minimum clearance required to remove bowl

Sub-Compact with Transparent Bowl

Port Size	Flow (SCFM)	Semi-Automatic Drain		Manual Drain	
		Part #	Price/E	Part #	Price/E
1/4"	80	B72G-2AG	\$204.30	B72G-2MG	\$142.05
3/8"	80	B72G-3AG	207.65	B72G-3MG	146.80

Sub-Compact with Metal Bowl and Sight Glass

Port Size	Flow (SCFM)	Semi-Automatic Drain		Manual Drain	
		Part #	Price/E	Part #	Price/E
1/4"	80	B72G-2AG-MB	\$218.45	B72G-2MG-MB	\$157.95
3/8"	80	B72G-3AG-MB	222.50	B72G-3MG-MB	161.70

Features:

- particle removal per ISO 8573-1, Class 5 and Class 3
- pressure range 5-150 PSI
- in-line or modular installation
- 40 micron element
- 3.5 oz. reservoir
- quick-release bayonet bowl
- prismatic lens liquid level indicator
- supplied with GC230 gauge
- inlet pressure:
 - transparent bowl: **150 PSI** at ambient temperature (70°F)
 - metal bowl: **250 PSI** at ambient temperature (70°F)

Compact with Transparent Bowl

Port Size	Flow (SCFM)	Automatic Drain		Manual Drain	
		Part #	Price/E	Part #	Price/E
1/4"	78	B73G-2AG	\$288.30	B73G-2MG	\$215.45
3/8"	123	B73G-3AG	288.30	B73G-3MG	215.45
1/2"	123	B73G-4AG	288.30	B73G-4MG	215.45

Compact with Metal Bowl and Sight Glass

Port Size	Flow (SCFM)	Automatic Drain		Manual Drain	
		Part #	Price/E	Part #	Price/E
1/4"	78	B73G-2AG-MB	\$297.50	B73G-2MG-MB	\$224.65
3/8"	123	B73G-3AG-MB	294.85	B73G-3MG-MB	224.65
1/2"	123	B73G-4AG-MB	297.50	B73G-4MG-MB	221.70

Features:

- pressure range 5-125 PSI
- 40 micron element
- 7 oz. reservoir
- relieving type
- supplied with GC230 gauge
- inlet pressure:
 - transparent bowl: **150 PSI** at ambient temperature (70°F)
 - metal bowl: **250 PSI** at ambient temperature (70°F)

Standard with Transparent Bowl and Guard

Port Size	Flow (SCFM)	Automatic Drain		Manual Drain	
		Part #	Price/E	Part #	Price/E
3/8"	163	B74G-3AG	\$342.35	B74G-3MG	\$266.55
1/2"	212	B74G-4AG	339.40	B74G-4MG	263.05
3/4"	212	B74G-6AG	339.40	B74G-6MG	264.20

Standard with Metal Bowl and Sight Glass

Port Size	Flow (SCFM)	Automatic Drain		Manual Drain	
		Part #	Price/E	Part #	Price/E
3/8"	163	B74G-3AG-MB	\$347.30	B74G-3MG-MB	\$271.30
1/2"	212	B74G-4AG-MB	339.60	B74G-4MG-MB	267.70
3/4"	212	B74G-6AG-MB	372.90	B74G-6MG-MB	267.70

See page 260 for filter/regulator accessories.



FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings given at 150 PSIG inlet pressure.



with transparent bowl



with metal bowl



with transparent bowl



with metal bowl



with guard



with metal bowl