# 250 Lb. Steam Ball Valves

### Application:

 recommended for use with fluids with widely varying temperatures and/or thermal expansion rates

#### Features:

- pressure rating: 600 PSI; 250 PSI saturated steam
- vacuum service to 29 inches Hg
- bronze body
- 316 stainless steel ball and stem
- blow-out proof stem design
- multi-fill RPTFE seats
- multi-fill stuffing box ring
- high temperature MTFE stem packing
- adjustable packing gland
- maximum temperature: 406°F

#### female NPT x female NPT

Size	Port	Bronze	
		Part #	Price/E
1/2"	full	BBV50ST	\$78.20
3/4"	standard	BBV75ST	126.00
1"	standard	BBV100ST	147.95
2"	standard	BBV200ST	410.55

## Safety Vented Ball Valves

- Applications:
- for air service only
- vent downstream air in accordance with OSHA regulation 1910.147 for pneumatic systems **Features:**
- pressure rating: 600 PSI
- brass valve
- chromium plated ball
- RTFE seats and stuffing box ring
- blow-out proof stem design
- adjustable packing gland

#### female NPT x female NPT

Size	Port	Brass	
		Part #	Price/E
1/4 "	full	BBV25LV	\$52.45
3/8"	full	BBV38LV	52.45
1/2"	full	BBV50LV	52.45
3/4"	standard	BBV75LV	75.70
1"	standard	BBV100LV	96.65
11⁄4"	standard	BBV125LV	152.75
11⁄2"	standard	BBV150LV	187.15
2"	standard	BBV200LV	227.20

## Bronze Ball Valves with NPT Tap for Drain

### Application:

- recommended for water and air service
- Features:
- pressure rating: 125 PSI WOG
- vent downstream air in accordance with OSHA regulations for pneumatic systems
- chromium plated ball
- RTFE seats and stuffing box ring
- blow-out proof stem
- adjustable packing gland
- auto-drain / auto-vent
- 1/4" NPT tapped port provides additional options such as an air venting elbow or noise muffler female NPT x female NPT

Size	Port	Bronze	
		Part #	Price/E
1⁄4"	full	BBV25VT	\$55.70
3/8"	full	BBV38VT	55.70
1/2"	full	BBV50VT	55.70
3/4"	full	BBV75VT	112.65
1"	full	BBV100VT	157.80



