Valves

Button



Thread	Bra	ass
	Part #	Price/E
1/4" NPT female	BV2F	\$24.75
1/4" NPT male	BV2M	24.75

Tank Filler









Applications:


used on compressed air tanks and other applications

· standard valve stem thread

Connection	Longth	Nickel Plated		Longth	Brass	
	Length	Part #	Price/E	Length	Part #	Price/E
½" NPT	.85"	TFV1S	\$5.10			
	1.24"	TFV1L	6.30			
1⁄4" NPT	1"	TFV2	5.95			
1⁄4" barb				1.57"	TFV2HB	\$8.45

Brass Lever External Drains

Application:





TFV1L



• maximum operating pressure: 30 PSI at ambient temperature 70°F (21°C)

Female NPT	Male NPT	Brass		
		Part #	Price/E	
1/4"	1/4"	LDC2	\$32.00	



Male NPT	Male NPT	Brass		
		Part #	Price/E	
1/4"	1/4"	LDCM2	\$35.50	



Ī	Female NPT	Female NPT	Bra	ass
			Part #	Price/E
	1/4"	1/4"	LDCF2	\$34.00

Brass External Drain Cocks

Applications:

• designed for low pressure water and air applications



• maximum operating pressure: 150 PSI at ambient temperature (70°F (21°C)

NDT Sizo	Bra	ass
NPT Size	Part #	Price/E
1/8"	D02	\$3.50
1/4"	D04	5.05



