


## Hot Water Washdown Spray Nozzles

### Applications:

For low pressure cleaning and sanitation applications including food and dairy processing, tank and drum cleaning, pharmaceutical and chemical manufacturing and meat and poultry packing.

### Features:

- designed for operator comfort
- variable spray pattern from solid stream to 50° hollow cone
- hose connects at base of gun for easy maneuvering
- ½" female NPT inlet
- rubber coated handle protects hands from water temperatures to **150°F**
- **12.5 GPM** flow capacity at **150 PSI**
- *Do not use with steam lines.* 



Cover Color	Brass		Aluminum	
	Part #	Price/E	Part #	Price/E
black	<b>BWSG</b>	<b>\$269.40</b>	<b>AWSG</b>	<b>\$288.75</b>
white	<b>BWSG-W</b>	<b>295.95</b>	<b>AWSG-W</b>	<b>309.05</b>


## Swivel Connectors for Washdown Spray Guns

### Features:

- 300 series stainless steel swivel connector for stainless spray nozzles
- 360° ball type swivel adapter helps prevent hose kinking

### Ball Type Swivel x Hose Shank

NPT	Hose ID	Part #	Price/E
½"	½"	<b>SSA44</b>	<b>\$206.00</b>
½"	⅝"	<b>SSA54</b>	<b>206.00</b>
½"	¾"	<b>SSA64</b>	<b>206.00</b>



### Features:

- swivel body
- EPDM gasket

### Straight Swivel x Hose Shank

NPT	Hose ID	Brass		Stainless Steel	
		Part #	Price/E	Part #	Price/E
½"	½"	<b>BNS44</b>	<b>\$61.90</b>	<b>BNS44SS</b>	<b>\$81.40</b>
½"	¾"	<b>BNS64</b>	<b>61.90</b>	<b>BNS64SS</b>	<b>110.45</b>



### Straight Swivel x GHT Thread

NPT	Female GHT	Brass Part #	Price/E
½"	¾"	<b>BMAS974</b>	<b>\$61.90</b>



## Thermal-Gard™ Elevated Temperature Spray Nozzle

### Features:

- Thermal-Gard™ elevated temperature spray nozzle protects the operator from extreme hot water temperatures that exceed the comfort zone of standard hot water nozzles.
- Assembly includes required special rigid, stainless steel adapter, (⅜" male NPT x ½" female NPT).
- Thermal insulating sleeve reduces overall heat during elevated temperature conditions.
- Stainless steel lever handle is coated for additional thermal protection and operator comfort.
- Lightweight aluminum alloy body reduces overall weight
- Aluminum alloy body is electrolessly nickel plated for additional corrosion protection
- Recommended for water temperatures above **140°F** to a maximum temperature of **200°F**.
- **12.5 GPM** flow capacity
- working pressure: **150 PSI**
- ⅜" female NPT inlet
- black cover



Aluminum	
Part #	Price/E
<b>AWSG-TG</b>	<b>\$355.80</b>