

Dry Can Specialty Belt



1 Multiple cord plies for greater strength and durability.

2 Notched design for greater flexibility and increased life.


Unique deep groove
for drying machines

Notched for
better flexibility

Applications:
Textile industry
Drying cans

Recommended Pulleys:
Conventional – OD, Taper Bushed, or MST (C)

Dry Can Specialty Belt



Part Number Example: **CC600S** = **CC** **600** **S**
Cross Section Double Angle Pitch Length (inches) Notched Cog Construction

The original deep-groove notched design is specifically developed for the demanding textile industry double angle "CC" drives.

Deep groove double "CC" belts are designed for drives with long center, serpentine applications. Dry Can specialty belts are notched for added flexibility.

Important Application Information

Dry Can belts are normally used as a single belt on a drive and matching is not required. When ordering two or more Dry Can belts to be used as a matched set on the same drive, please specify that the belts must be a matched set.

Dry Can Specialty Belt Part Numbers

Part Number	Pitch Length (in)	Weight (lbs)
C Belt Recommended Pulleys: Conventional – QD, Taper Bushed, or MST (C)		
CC210S	214.1	7.97
CC240S*	242.1	9.02
CC270S*	272.1	10.14
CC300S*	302.1	11.25
CC330S	332.1	12.37
CC360S	362.1	13.49
CC390S*	392.1	14.61
CC420S	422.1	15.73
CC440S	442.1	16.47
CC450S*	452.1	16.84
CC480S	482.1	17.96
CC540S	542.1	20.20
CC550S	552.1	20.57
CC600S	602.1	22.43
CC640S	642.1	23.92
CC660S	662.1	24.67
CC670S	672.1	25.04
CC680S*	682.1	25.41
CC700S*	702.1	26.16
CC720S	722.1	26.91
CC750S	752.1	28.02
CC780S	782.1	29.14
CC800S*	802.1	29.89
CC840S	842.1	31.38
CC900S	902.1	33.61

* Non-stock item. Minimum order quantity and/or extended lead times may apply. Contact customer service for availability.

For sizes not listed contact customer service for availability.