


M-11868 2

GENERAL INFORMATION			
WIRE LOCATION	WIRE	WIRE COLOR	WIRE SIZE (AWG)
1	-	-	-
2	-	-	-
3	GROUND (G)	GREEN	#12
4	-	-	-
5	NEUTRAL (N1)	WHITE	#12
6	LINE (L1)	BLACK	#12
7	-	-	-
8	-	-	-

NOTES:
 1. RATING: 20A 120/208 V.
 2. ALL DIMENSIONS ARE IN INCHES [mm] EXCEPT THE FLEXIBLE METAL CONDUIT LENGTH IN FOOT.

LIST OF PARTS		
DESCRIPTION	MATERIAL	FINISH
MALE CONNECTOR	THERMOPLASTIC	BLACK
FEMALE CONNECTOR	THERMOPLASTIC	BLACK
CONDUIT	GALV. STEEL	
CLAMP	STEEL	ZINC PLATE
RIVET	STEEL	ZINC PLATE
INSULATOR	THERMOPLASTIC	
WIRE	COPPER	



REPAIRABLE <input type="checkbox"/>	NON-REPAIRABLE <input checked="" type="checkbox"/>
-------------------------------------	--

2	UPDATE THE PRINT PER DCN #21027.	2/5/15
1	NEW RELEASE PER DCN #20674	6/17/14
SYM	REVISIONS	APP DATE

THE DESIGN AND DIMENSIONS OF THE PRODUCT SHOWN ON THIS DRAWING ARE SUBJECT TO CHANGE WITHOUT NOTICE

TITLE MODULAR WIRING EXTENDER CABLE 1/1/1 MALE TO FEMALE	
TOLERANCES UNLESS OTHERWISE SPECIFIED .XX = ±.01 .XXX = ±.005 ANGLES = ±2°	WIRING DEVICE-KELLEMS HUBBELL INCORPORATED SHELTON, CT DR. BY DMP APP. BY TR. BY SCALE NONE CHK. BY DATE 2/3/11

CATALOG NUMBER	DESCRIPTION	"L" LENGTH
CEXT111MFL01	EXT CABLE. 1/1/1 (1 HOT, 1 NEUTRAL, 1 GROUND), MALE TO FEMALE	1-FT.
CEXT111MFL05		5-FT.
CEXT111MFL10		10-FT.
CEXT111MFL15		15-FT.
CEXT111MFL20		20-FT.
CEXT111MFL25		25-FT.
CEXT111MFL30	30-FT.	

DIMENSION SHEET FOR CAT. NO. SEE TABLE REPAIRABLE NON-REPAIRABLE B M-11868 2