

BALDOR® • RELIANCE

Product Information Packet

CHM344A

.5HP,1725RPM,3PH,60HZ,48YZ,3416M,TEAO,F1

Part Detail							
Revision:	B	Status:	PRD/A	Change #:		Proprietary:	No
Type:	AC	Prod. Type:	3416M	Elec. Spec:	34WGR073	CD Diagram:	CD0007
Enclosure:	TEAO	Mfg Plant:		Mech. Spec:	34M250	Layout:	34LYM250
Frame:	48YZ	Mounting:	F1	Poles:	04	Created Date:	06-17-2013
Base:	RS	Rotation:	R	Insulation:	B	Eff. Date:	10-02-2014
Leads:	12#18					Replaced By:	
Literature:		Elec. Diagram:					

Nameplate NP1257L									
CAT.NO.	CHM344A								
SPEC.	34M250R073G1								
HP	.5								
VOLTS	230/460								
AMP	2.2/1.1								
RPM	1725								
FRAME	48YZ	HZ			60	PH	3		
SER.F.	1.25	CODE			M	DES	B	CL	B
NEMA-NOM-EFF	66	PF			63				
RATING	40C AMB-CONT								
CC		USABLE AT 208V			2.3				
DE	6203	ODE			6203				
ENCL	TEAO	SN							
	SFA 2.4/1.2								

Parts List		
Part Number	Description	Quantity
SA264743	SA 34M250R073G1	1.000 EA
RA251449	RA 34M250R073G1	1.000 EA
11XT0832G06	8-32 X 3/8 TY 23 TAPPING	1.000 EA
LD5000A52	LEAD ASSY W/INTERNAL STAR RING TERMINALS	1.000 EA
11XT1032A06	10-32 X 3/8 HX WSHR HD SLTD TYPE 23	2.000 EA
34EP3204A01SP	FR ENDPLATE, MACH	1.000 EA
WD4100A01	DP-875 HEYCO PLUG OR 62MP0875 MICRO PLAS	1.000 EA
RM1001A01	GROMMET "MIDSTATES"	1.000 EA
SP1000A01	TERM BOARD, MODEL 34 SW	1.000 EA
51XW0832A07	8-32 X .44, TAPTITE II, HEX WSHR SLTD SE	3.000 EA
RM1000A03SP	CUSHION RING, MDL 17-33-34	1.000 EA
HA6004A01A	CLAMP CUSHION RING ASSY	1.000 EA
HW5100A03SP	WAVY WASHER (W1543-017)	1.000 EA
34EP3205B01	PU ENDPLATE, MACH	1.000 EA
RM1000A03SP	CUSHION RING, MDL 17-33-34	1.000 EA
HA6004A01A	CLAMP CUSHION RING ASSY	1.000 EA
XY0832A02	8-32 HEX NUT	4.000 EA
34CB4501SP	TERMINAL BOX LID, STAMPED X (PLATED)	1.000 EA
34GS1005	GASKET, TERM PLATE LID	1.000 EA
51XW0832A07	8-32 X .44, TAPTITE II, HEX WSHR SLTD SE	2.000 EA
10XF0440S02	04-40 X 1/8 TYPE F HEX HD STAINLESS STIC	2.000 EA
34BA4001A01A	RESILIENT BASE, 408-416 AUTOPHORETIC	1.000 EA
HA3169A17	THRUBOLT #8-32 THDS X 8.375" LONG	4.000 EA
LB1118	LABEL,WARNING (ROLL LABEL)	1.000 EA

Parts List (continued)		
Part Number	Description	Quantity
MN416A01	TAG-INSTAL-MAINT no wire (1200/bx) 10/13	1.000 EA
LB1506	LABEL "AMERICAN MADE" 1.50 X 1.00	1.000 EA
LB1125C01	STD (STOCK) CARTON LABEL BALDOR WITH FLA	1.000 EA
LC0007	CONNECTION LABEL	1.000 EA
NP1257L	ALUM UL CSA CC THERMAL REV MTG	1.000 EA
PA1000	PACKING GROUP 3500 SHORT	1.000 EA

AC Induction Motor Performance Data

Record # 42463 - Typical performance - not guaranteed values


Winding: 34WGR073-R001	Type: 3416M	Enclosure: TEAO
-------------------------------	--------------------	------------------------

Nameplate Data				460 V, 60 Hz: High Voltage Connection	
Rated Output (HP)	.5 AIR OVER			Full Load Torque	1.53 LB-FT
Volts	230/460			Start Configuration	direct on line
Full Load Amps	2.2/1.1			Breakdown Torque	6.36 LB-FT
R.P.M.	1725			Pull-up Torque	4.73 LB-FT
Hz	60	Phase	3	Locked-rotor Torque	5.62 LB-FT
NEMA Design Code	B	KVA Code	M	Starting Current	6.84 A
Service Factor (S.F.)	1.25			No-load Current	0.883 A
NEMA Nom. Eff.	66	Power Factor	63	Line-line Res. @ 25°C	34.071 Ω
Rating - Duty	40C AMB-CONT			Temp. Rise @ Rated Load	
S.F. Amps	2.4/1.2			Temp. Rise @ S.F. Load	
				Rotor inertia	0.0381 LF ²


Load Characteristics 460 V, 60 Hz, 0.5 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	32	45	54	63	69	74	69
Efficiency	41.7	55.9	63.3	67	69.3	69.8	69.3
Speed	1781.1	1767.1	1754.9	1739.5	1725.4	1709	1725
Line amperes	0.899	0.954	1.03	1.12	1.22	1.34	1.22


Performance Graph at 460V, 60Hz, 0.5HP Typical performance - Not guaranteed values



12/17/2014 ACPERF, record # 42463



CD0007



1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
2. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY VARY.
3. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

3PH, DV, THERMAL, 12 LEADS