# Clear PVC Tubing

Applications:

Clear PVC Tubing is designed to be used with standard shank fittings in low pressure liquid and pneumatic applications.

## Features:

### domestic

- for non-critical hospital use such as suction and draining
- produced from FDA materials, but not FDA approved shipped in individually boxed bundles, sold only in lengths shown below
- maximum temperature: 135°F

Size		Working Pressure	Longth	PVC	
ID	OD	(PSI) @ 72°F	Length	Part #	Price/E
3/16"	5/16"	55	100'	CL0305	\$43.25
1/4"	3/8"	55	100'	CL0406	50.60
1/4"	1/2"	70	100'	CL0408	113.00
5/16"	7/16"	50	100'	CL0507	58.60
3/8"	1/2"	40	100'	CL0608	72.25
3/8"	5/8"	65	100'	CL0610	149.00
1/2"	5/8"	30	100'	CL0810	97.00
1/2"	3/4"	45	100'	CL0812	180.00
5/8"	7/8"	40	100'	CL1014	224.00
3/4"	1"	35	100'	CL1216	258.00
1"	1-1/4"	28	100'	CL1620	340.00
1-1/4"	1-3/4"	45	50'	CL2028-50	430.00
1-1/2"	2"	40	50'	CL2432-50	500.00



## imported

### Features:

- temperature range: 14°F to 149°F
- shipped in bundles wrapped with PVC film, sold only in lengths shown below

Size		Working Pressure		PVC	
ID	OD	(PSI) @ 72°F	Length	Part #	Price/E
1/4"	3/8"	50	100'	ICL0406	\$25.50
3/8"	1/2"	35	100'	ICL0608	35.45
1/2"	5/8"	35	100'	ICL0810	46.30
1/2"	3/4"	50	100'	ICL0812	96.55
3/4"	1"	35	100'	ICL1216	136.90
1"	1¼"	30	100'	ICL1620	178.55
1½"	2"	15	50'	ICL2432	290.55

# Clear PVC Braided Tubing

# Applications:

Clear PVC Braided Tubing is designed to be used in low pressure liquid and pneumatic applications.

# Features:

### domestic

Working Pressure

- high grade tensile strength polyester yarn reinforcement temperature range: 27°F to 150°F

Size

shipped in coils, sold only in lengths shown below

ID	OD	(PSI) @ 72°F	Lengui	Part #	Price/E
3/16"	3/8"	250	300'	BR0306	\$299.50
1/4"	7/16"	250	300'	BR0446	335.00
3/8"	5/8"	225	300'	BR0609	633.25
1/2"	3/4"	200	300'	BR0812	530.00
5/8"	7/8"	200	300'	BR1014	820.00
3/4"	1-1/16"	150	300'	BR1218	820.00
1"	1-5/16"	125	200'	BR1621	1362.00
1-1/4"	1-11/16"	100	100'	BR2027	850.00
1-1/2"	1-15/16"	100	100'	BR2431	1737.00

PVC



### imported

- for various machine tools and the transportation of chemicals temperature range: 14°F to 149°F
- shipped in bundles wrapped with PVC film, sold only in lengths shown below

Size		Working Pressure	Longth	PVC	
ID	OD	(PSI) @ 72°F	Length	Part #	Price/E
1/4"	1/2"	142	300'	IBR0446	\$191.00
3/8"	5/8"	114	300'	IBR0609	246.25
1/2"	3/4"	100	300'	IBR0812	310.00
3/4"	1-1/16"	71	300'	IBR1218	661.30
1"	1-5/16"	71	200'	IBR1621	513.10