

King Crimp Style Sleeves



Only use the crimp style shanks with the crimp style sleeves and ferrules. Due to differences in dimensions and tolerances for safety reasons, do not interchange other manufacturer's products with Dixon products.



Hose ID	Hose OD		Carbon Steel		304 Stainless Steel		Work. Pressure (PSI)		Sleeve ID	Sleeve Wall Thickness	Sleeve Overall Length
	From	To	Part #	Price	Part #	Price	cam & groove ¹	KC nipple ²			
3"	3-13/64"	3-16/64"	CS300-1CS	\$10.05	CS300-1SS	\$17.05	125	200	3.313"	.090"	3¾"
	3-17/64"	3-20/64"	CS300-2CS	10.05	CS300-2SS	17.05	125	200	3.375"	.090"	3¾"
	3-21/64"	3-24/64"	CS300-3CS	10.05	CS300-3SS	17.05	125	200	3.438"	.090"	3¾"
	3-25/64"	3-28/64"	CS300-4CS	10.05	CS300-4SS	17.05	125	200	3.500"	.090"	3¾"
	3-29/64"	3-32/64"	CS300-5CS	10.05	CS300-5SS	17.05	125	200	3.563"	.090"	3¾"
	3-33/64"	3-36/64"	CS300-6CS	10.05	CS300-6SS	17.05	125	200	3.625"	.090"	3¾"
	3-37/64"	3-40/64"	CS300-7CS	10.05	CS300-7SS	17.05	125	200	3.688"	.090"	3¾"
	3-41/64"	3-44/64"	CS300-8CS	10.05	CS300-8SS	17.05	125	200	3.750"	.090"	3¾"
	3-45/64"	3-48/64"	CS300-9CS	10.05	CS300-9SS	17.05	125	200	3.813"	.090"	3¾"
	3-49/64"	3-52/64"	CS300-10CS	10.05	CS300-10SS	17.05	125	200	3.875"	.090"	3¾"
	3-53/64"	3-56/64"	CS300-11CS	10.05	CS300-11SS	17.05	125	200	3.938"	.090"	3¾"
	3-57/64"	3-60/64"	CS300-12CS	10.05	CS300-12SS	17.05	125	200	4.000"	.090"	3¾"
	3-61/64"	4"	CS300-13CS	10.05	CS300-13SS	17.05	125	200	4.063"	.090"	3¾"
	4-1/64"	4-4/64"	CS300-14CS	10.05	CS300-14SS	17.05	125	200	4.125"	.090"	3¾"
	4-5/64"	4-8/64"	CS300-15CS	10.05	CS300-15SS	17.05	125	200	4.188"	.090"	3¾"
	4-9/64"	4-12/64"	CS300-16CS	10.05	CS300-16SS	17.05	125	200	4.250"	.090"	3¾"
4"	4-13/64"	4-16/64"	CS400-1CS	13.55	CS400-1SS	28.35	110	175	4.313"	.090"	3¾"
	4-17/64"	4-20/64"	CS400-2CS	13.55	CS400-2SS	28.35	110	175	4.375"	.090"	3¾"
	4-21/64"	4-24/64"	CS400-3CS	13.55	CS400-3SS	28.35	110	175	4.438"	.090"	3¾"
	4-25/64"	4-28/64"	CS400-4CS	13.55	CS400-4SS	28.35	110	175	4.500"	.090"	3¾"
	4-29/64"	4-32/64"	CS400-5CS	13.55	CS400-5SS	28.35	110	175	4.563"	.090"	3¾"
	4-33/64"	4-36/64"	CS400-6CS	13.55	CS400-6SS	28.35	110	175	4.625"	.090"	3¾"
	4-37/64"	4-40/64"	CS400-7CS	13.55	CS400-7SS	28.35	110	175	4.688"	.090"	3¾"
	4-41/64"	4-44/64"	CS400-8CS	13.55	CS400-8SS	28.35	110	175	4.750"	.090"	3¾"
	4-45/64"	4-48/64"	CS400-9CS	13.55	CS400-9SS	28.35	110	175	4.813"	.090"	3¾"
	4-49/64"	4-52/64"	CS400-10CS	13.55	CS400-10SS	28.35	110	175	4.875"	.090"	3¾"
	4-53/64"	4-56/64"	CS400-11CS	13.55	CS400-11SS	28.35	110	175	4.938"	.090"	3¾"
	4-57/64"	4-60/64"	CS400-12CS	13.55	CS400-12SS	28.35	110	175	5.000"	.090"	3¾"
	4-61/64"	5"	CS400-13CS	13.55	CS400-13SS	28.35	110	175	5.063"	.090"	3¾"
	5-1/64"	5-4/64"	CS400-14CS	13.55	CS400-14SS	28.35	110	175	5.125"	.090"	3¾"
	5-5/64"	5-8/64"	CS400-15CS	13.55	CS400-15SS	28.35	110	175	5.188"	.090"	3¾"
	5-9/64"	5-12/64"	CS400-16CS	13.55	CS400-16SS	28.35	110	175	5.250"	.090"	3¾"
6"	6-21/64"	6-28/64"	CS600-1CS	37.90	CS600-1SS	72.75	*	*	6.500"	.120"	5½"
	6-29/64"	6-36/64"	CS600-2CS	37.90	CS600-2SS	72.75	*	*	6.625"	.120"	5½"
	6-37/64"	6-44/64"	CS600-3CS	37.90	CS600-3SS	72.75	*	*	6.750"	.120"	5½"
	6-45/64"	6-52/64"	CS600-4CS	37.90	CS600-4SS	72.75	*	*	6.875"	.120"	5½"
	6-53/64"	6-60/64"	CS600-5CS	37.90	CS600-5SS	72.75	*	*	7.000"	.120"	5½"
	6-61/64"	7-4/64"	CS600-6CS	37.90	CS600-6SS	72.75	*	*	7.125"	.120"	5½"
	7-5/64"	7-12/64"	CS600-7CS	37.90	CS600-7SS	72.75	*	*	7.250"	.120"	5½"
	7-13/64"	7-20/64"	CS600-8CS	37.90	CS600-8SS	72.75	*	*	7.375"	.120"	5½"
	7-21/64"	7-28/64"	CS600-9CS	37.90	CS600-9SS	72.75	*	*	7.500"	.120"	5½"

* consult Dixon for pressure rating

¹ based on using crimp cam and groove shanks

² based on using King combination nipples