

Check Valves

Features:

- Class 800
- ASTM A105, ANSI B120.1
- bolted bonnet
- pressure rating: **1975 PSI**
- maximum temperature: **800°F**
- can be used for steam service

Female NPT	Part #	Price/E
1/2"	FSCV50	\$128.40
3/4"	FSCV75	144.45
1"	FSCV100	202.60
1 1/4"	FSCV125	353.05
1 1/2"	FSCV150	375.10
2"	FSCV200	451.35



Spring-Loaded Check Valves

Features:

- cracking pressure: 0.50 PSI
- NBR seat
- soft seat for bubble tight shutoff, spring loaded for fast seating action
- flow profile designed to minimize head loss
- pressure rating: 1/2" - 2" **400 PSI** WOG; 3" - 4" **175 PSI** WOG
- temperature range: **10°F to 210°F** (-10°C to 100°C)

Female NPT	Part #	Price/E
1/2"	CV050	\$18.60
3/4"	CV075	25.00
1"	CV100	34.00
1 1/4"	CV125	53.00
1 1/2"	CV150	79.30
2"	CV200	112.75
3"	CV300	355.90
4"	CV400	550.00




Strainer with Spring-Loaded Check Valves

Features:

- cracking pressure: 0.50 PSI
- NBR seat
- stainless steel strainer
- soft seat for bubble tight shutoff, spring loaded for fast seating action
- flow profile designed to minimize head loss
- pressure rating: 1 1/2" - 2" **400 PSI** WOG; 3" - 4" **175 PSI** WOG
- temperature range: **10°F to 210°F** (-10°C to 100°C)

Female NPT	Part #	Price/E
1 1/2"	BVFS20	\$89.60
2"	BVFS25	129.00
3"	BVFS35	379.50
4"	BVFS40	572.50



Q